

MISSION RISE

Project № 19011

February 2019

**TRAFFIC IMPACT ANALYSIS
LAKE COUNTY
FLORIDA**

Prepared by:



Traffic & Mobility Consultants

3101 Maguire Boulevard, Suite 265

Orlando, Florida 32803

www.trafficmobility.com

(407) 531-5332

Prepared for:

Hanover Land Company LLC

605 Commonwealth Avenue

Orlando, Florida 32803

EXECUTIVE SUMMARY

Project Information

Name: Mission Rise
Location: West of SR 19, south of number 2 Road, Howey-in-the-Hills, Florida
Description: 629 Single Family Residential Units

Findings

Trip Generation: 5,648 New Daily Trips / 453 AM Peak Hour Trips / 591 PM Peak Hour Trips

Roadway Capacity: Study segments currently operate within their adopted Level of Service (LOS) standards and will continue to do so at project buildout.

Intersection Capacity The intersections of SR 19 & CR 48 and US 27 & Florida Turnpike Ramps will require modifications to the signal timing and phasing plans in order to operate adequately.

The 2-Way Stop controlled intersections of SR 19 and Central and SR 19 and CR 455 should be monitored in the future for a possible signal warrant.

The intersection of SR 19 and Orange Blossom Road should be improved by the addition of a northbound left turn lane and a southbound right turn lane by the start of Phase 2 of the project.

Access Review: The proposed development will be accessed as follows:

- Project Access #1 at Number 2 Road
- Project Access #2 at SR 19 (Main Entrance)
- Project Access #3 at Orange Blossom Road

Southbound right turn lane and northbound left turn lane on SR 19 at project access #2 (main entrance) are warranted at this intersection, the recommended right turn lane and left turn lane lengths are 405 feet and 465 feet, respectively.

PROFESSIONAL ENGINEERING CERTIFICATION

I hereby certify that I am a Professional Engineer properly registered in the State of Florida practicing with Traffic & Mobility Consultants LLC, a corporation authorized to operate as an engineering business, CA-30024, by the State of Florida Department of Professional Regulation, Board of Professional Engineers, and that I have prepared or approved the evaluations, findings, opinions, conclusions, or technical advice attached hereto for:

PROJECT: Mission Rise

LOCATION: Lake County, Florida

CLIENT: Hanover Land Company, LLC

I hereby acknowledge that the procedures and references used to develop the results contained in these computations are standard to the professional practice of Transportation Engineering as applied through professional judgment and experience.

TABLE OF CONTENTS

	Page
1.0 INTRODUCTION.....	1
1.1 Study Area.....	1
2.0 EXISTING CONDITIONS ANALYSIS	4
2.1 Roadway Segment Capacity.....	4
2.2 Intersection Capacity	6
3.0 PROJECT TRAFFIC	9
3.1 Trip Generation.....	9
3.2 Trip Distribution/Assignment	9
4.0 PROJECTED CONDITIONS ANALYSIS	11
4.1 Background Traffic Projection	11
4.2 Roadway Segment Capacity.....	11
4.3 Intersection Capacity Analysis	13
5.0 ACCESS REVIEW	16
5.1 Turn Lane Review.....	16
6.0 STUDY CONCLUSIONS.....	18
APPENDICES.....	19
Appendix A Study Methodology & LSMPO Comments	
Appendix B Preliminary Development Plan	
Appendix C 2018 Lake County TMS & FDOT High-plan Service Volume	
Appendix D Turning Movement Counts & Seasonal Factor Data	
Appendix E HCM Analysis Worksheets - Existing Conditions & Signal Timings	
Appendix F ITE Trip Generation Sheets	
Appendix G CFRPM Model Output	
Appendix H Growth Trend Analysis & Historical Traffic Counts	
Appendix I HCM Worksheets – Projected Conditions & Intersection volume Projection	
Appendix J FDOT Design Manual Exhibit FDM 212.1	
Appendix K NCHRP Report 457	

LIST OF TABLES

Table 1 Study Area	3
Table 2 Existing Roadway Segment Capacity Analysis	5
Table 3 Existing Intersection Capacity Analysis	6
Table 4 Trip Generation Analysis	9
Table 5 Projected Roadway Segment Capacity Analysis	12
Table 6 Projected Intersection Capacity Analysis	13

LIST OF FIGURES

Figure 1 Site Location Map	2
Figure 2 Existing AM Peak Intersection Volumes	7
Figure 3 Existing PM Peak Intersection Volumes	8
Figure 4 Project Trip Distribution	10
Figure 5 Projected AM Peak Intersection Volumes	14
Figure 6 Projected PM Peak Intersection Volumes	15

1.0 INTRODUCTION

This Traffic Impact Study (TIS) was conducted to assess the impact of the proposed Mission Rise development in the town of Howey-in-the-Hills, Lake County, Florida. The proposed development is a residential community with 629 single family units, which will be built in three phases (approximately 210 units per phase) with an anticipated build out year of 2024. The site is located north of the intersection of SR 19 and E Dewey Robbins Road. **Figure 1** depicts the site location and the surrounding transportation network. The analysis was prepared in accordance with the methodology submitted to the Town of Howey-in-the-Hills and reviewed by Lake-Sumter Metropolitan Planning Organization (LSMPO). The methodology comments were addressed in this TIA. Copies of the methodology and the LSMPO comments are included in **Appendix A**.

The development will be accessed via three (3) proposed driveways on SR 19, Number 2 Road and Orange Blossom Road. The preliminary development site plan is provided in **Appendix B**.

Data used in the analysis consisted of site plan/development information provided by the Project Engineers, AM and PM peak hour intersection traffic counts obtained by Traffic & Mobility Consultants LLC, and roadway capacities obtained from the Lake County TMS Segment Report and from FDOT for SR 19.

1.1 Study Area

The project study area was established based on the standard requirements of the Lake Sumter Metropolitan Planning Organization (LSMPO) methodology. In accordance with the requirements of Tier 2 TIS methodology, the impact area includes roadway segments and intersections within 4.55-mile radius in addition to roadways where development is expected to consume 5% or more of their adopted Level of Service (LOS) capacities. A HIGHPLAN Analysis was conducted for SR 19, from Taylor Memorial Cemetery to US 27, which is provided in **Appendix C**. The project study area determination is provided in **Table 1**.



**Table 1
Study Area**

Road Name	Segment	# LNS	A T	LOS Std	LOS Cap	Project Trips			Within 1 mile?	% Cap	In Study?
						%Dist	NB/EB	SB/WB			
SR 19	CR 452 (Main St) to CR 561	4	U	D	2,000	19%	71	41	NO	3.6%	NO
SR 19	CR 561 to Lake Harris North End	2	U	D	1,190	25%	93	55	NO	7.8%	YES
SR 19	Lake Harris North End to CR 48	2	T	D	1,200	25%	93	55	NO	7.8%	YES
SR 19	CR 48 to Central Ave	2	T	D	800	45%	167	99	NO	20.9%	YES
SR 19	Central Ave to Taylor Memorial Cemetery	2	T	D	800	45%	99	167	YES	20.9%	YES
SR 19	Taylor Memorial Cemetery to CR 455 (1)	2	T	C	900	46%	101	171	YES	19.0%	YES
SR 19	CR 455 to US 27/SR 25 (1)	2	T	C	900	35%	77	130	NO	14.4%	YES
SR 19	US 27/SR 25 to CR 478	2	T	C	850	5%	11	19	NO	2.2%	NO
CR 455	SR 19 to CR 561	2	T	D	1,200	15%	33	56	NO	4.7%	NO
CR 455	CR 561 to CR 561A	2	T	D	1,200	5%	11	19	NO	1.6%	NO
CR 48	US 27 to Lime Ave	2	U	D	792	25%	55	93	NO	11.7%	YES
CR 48	Lime Ave to SR 19	2	U	D	792	20%	44	74	NO	9.3%	YES
Orange Blossom Rd	Chris Rd to Revels Rd	2	T	D	612	0%	0	0	YES	0.0%	YES
Orange Blossom Rd	Revels Rd to SR 19	2	T	D	612	33%	72	123	YES	20.1%	YES
Number 2 Rd	Blue Sink Rd to Mare Ave	2	T	D	612	5%	19	11	YES	3.1%	YES
Central Ave	Mare Ave to SR 19	2	T	D	612	28%	104	61	YES	17.0%	YES
CR 561	SR19 to CR 448	2	U	D	792	1%	4	2	NO	0.5%	NO
CR 561	CR 448 to CR 48	2	U	D	792	2%	7	5	NO	0.9%	NO
CR 561	CR48 to South Astatula City Limit	2	T	D	720	2%	7	5	NO	1.0%	NO
CR 561	South Astatula City Limit to CR 455	2	T	D	720	10%	37	22	NO	5.1%	YES
CR 561	CR 455 to Howey Cross Rd	2	T	D	720	0%	0	0	NO	0.0%	NO

(1) FDOT QLOS HIGHPLAN Analysis for these segments of SR 19. Remaining capacities from LSMPO TMS Segment Report

Based on the information presented in **Table 1**, the study roadway segments are as follows:

- SR 19
 - SR 561 to Lake Harris North End
 - Lake Harris North End to CR 48
 - CR 48 to Central Avenue
 - Central Avenue to CR 455
 - CR 455 to US 27/SR25
- CR 48
 - US 27 to Lime Avenue
 - Lime Avenue to SR 19
- Orange Blossom Road
 - Revels Road to SR 19
- Number 2 Rd
 - Blue Sink Road to Mare Avenue
- Central Avenue
 - Blue Sink Road to Mare Avenue
- CR 561
 - South Astatula City Limit to CR 455

The study intersections are as follows:

- SR 19 at CR 48
- SR 19 at Central Avenue
- SR 19 at Florida Avenue
- SR 19 at CR 455
- US 27 at Turnpike Ramp
- US 27 at SR 19 Ramp

2.0 EXISTING CONDITIONS ANALYSIS

Existing conditions in the vicinity of the site were analyzed to establish a baseline for the traffic conditions prevailing in the vicinity of the proposed development. The analysis included a review of existing roadway segment capacity and analysis of the intersection operations at the study intersections.

2.1 Roadway Segment Capacity

Existing roadway conditions were analyzed by comparing the existing traffic volumes within the study area and the adopted level of service (LOS) standards for the roadway segments. **Table 2** summarizes the road segment capacity analysis.

Table 2
Existing Roadway Segment Capacity Analysis

Roadway Segment	Seg ID	No Lns	LOS Std	PH Dir Capacity	Dir	Exist Vol	LOS
SR 19							
CR 561 to Lake Harris North End	NA	4	D	1,190	NB SB	657 805	C C
Lake Harris North End to CR 48	NA	2	D	1,200	NB SB	657 805	C C
CR 48 to Central Ave	NA	2	D	800	NB SB	432 436	C C
Central Ave to Taylor Memorial Cemetery	NA	2	D	800	NB SB	432 436	C C
Taylor Memorial Cemetery to CR 455 (1)	NA	2	C	900	NB SB	508 503	B B
CR 455 to US 27/SR 25 (1)	NA	2	C	900	NB SB	526 541	C C
CR 48 (2)							
US 27 to Lime Ave	16	2	D	792	EB WB	366 483	C C
Lime Ave to SR 19	16	2	D	792	EB WB	366 483	C C
Orange Blossom Rd (2)							
Revels Rd to SR 19	NA	2	D	612	EB WB	8 13	C C
Number 2 Rd (2)							
Blue Sink Rd to Mare Ave	NA	2	D	612	EB WB	59 50	C C
Central Ave (2)							
Mare Ave to SR 19	NA	2	D	612	EB WB	59 50	C C
CR 561							
South Astatula City Limit to CR 455	16	2	D	720	EB WB	520 534	C C

Source: 2018 Lake County Annual Traffic Counts

(1) FDOT QLOS HIGHPLAN Analysis for these segments of SR 19

(2) Volumes Obtained from PM Peak Turning Movement Counts

The analysis indicates that all study roadway segments currently operate adequately within their LOS standard.



2.2 Intersection Capacity



The intersection capacity analysis was performed for the AM and PM peak hour periods. The capacity analysis was performed using the Synchro and the methods of the *Highway Capacity Manual (HCM), 6th Edition*. Turning movement volumes obtained during the AM and PM peak hour are displayed in **Figure 2**. Existing turning movement counts were collected during peak season; therefore, a seasonal adjustment factor was not applied. The turning movement counts and the seasonal factor report for Lake County are included in **Appendix D**.

The summary results of the intersection capacity analysis, summarized in **Table 3**, reveal that the intersection of SR 19 and CR 48 is currently operating inadequately during the PM peak hour. The remaining study intersections are currently operating at adequate LOS. Detailed *HCM* analysis worksheets are included in **Appendix E**.

Table 3
Existing Intersection Capacity Analysis

Intersection	Traffic Control	Time Period	EB		WB		NB		SB		Overall	
			Delay	LOS	Delay	LOS	Delay	LOS	Delay	LOS	Delay	LOS
SR 19 & CR 48	Signal	AM	--	--	11.1	B	20.5	C	74.6	E	46.6	D
		PM	--	--	10.8	B	20.1	C	133.6	F	90.5	F
SR 19 & Central Ave	TWSC	AM	22.7	C	19.2	C	--	--	--	--	--	--
		PM	23.7	C	19.6	C	--	--	--	--	--	--
SR 19 & Florida Ave	TWSC	AM	16.4	C	15.9	C	7.3	A	7.3	A	--	--
		PM	15.1	C	18.1	C	7.5	A	7.3	A	--	--
SR 19 & Revels Rd	TWSC	AM	0.0	A	11.4	B	--	--	--	--	--	--
		PM	14.7	B	10.7	B	--	--	--	--	--	--
SR 19 & Orange Blossom Rd	TWSC	AM	13.6	B	--	--	8.2	A	--	--	--	--
		PM	16.7	C	--	--	8.4	A	--	--	--	--
SR 19 & CR 455	TWSC	AM	--	--	19.1	C	--	--	8.6	A	--	--
		PM	--	--	21.6	C	--	--	8.8	A	--	--
US 27 & Florida Turnpike Ramps	Signal	AM	59.9	E	55.3	E	75.9	E	46.4	D	59.2	E
		PM	79.6	E	49.8	D	63.5	E	48.9	D	63.5	E
SR 19 Ramps & US 27	TWSC	AM	10.6	B	10.0	A	--	--	31.2	D	--	--
		PM	11.3	B	10.2	B	--	--	33.2	D	--	--





3.0 PROJECT TRAFFIC

3.1 Trip Generation

The traffic generation of the proposed development was calculated using the Institute of Transportation Engineers (ITE) *Trip Generation Manual, 10th Edition*. The trip generation for the project is summarized in **Table 4** and the ITE charts are provided in **Appendix F**.

Table 4
Trip Generation Analysis

ITE Code	Land Use	Size	Daily		AM Peak Hour				PM Peak Hour			
			Rate	Trips	Rate	Total	Enter	Exit	Rate	Total	Enter	Exit
210	Single-Family	629 DU	8.98	5,648	0.72	453	113	340	0.94	591	372	219

Trip generation analysis based on ITE Trip Generation Manual, 10th Edition
ITE equations were used as R^2 were greater than 0.75

The proposed development will generate 5,648 new trips per day, of which 453 trips occur during the AM peak hour and 591 trips occur during the PM peak hour.

3.2 Trip Distribution/Assignment

The Central Florida Regional Planning Model (CFRPM) based on the Florida Standard Transportation Model Structure (FSUTMS) was utilized to analyze the project's trip distribution percentages onto the roadway network. A plot of the model generated distribution pattern for the project is provided in **Appendix G**. Adjustments were made to the model generated distribution were applied to better reflect the surrounding transportation network, land uses, and known access routes. The final trip distribution pattern used in the analysis is illustrated in **Figure 3**.



4.0 PROJECTED CONDITIONS ANALYSIS

An analysis of projected conditions was conducted to determine the impact of the proposed development on the roadway segments capacity, as well as the proposed access connections and intersections to the site. The project buildout year for the analysis is 2024.

4.1 Background Traffic Projection

Projected background traffic was calculated for the buildout year 2024 by applying the historical growth rates for each study roadway. Historical traffic volumes were obtained from the County's traffic volume report and a growth trend analysis was performed for the study segments. The buildout traffic volume is the sum of the projected background traffic and the generated project trips. The detailed growth rate analysis and historical traffic counts are included in **Appendix H**.

4.2 Roadway Segment Capacity

Projected roadway conditions were analyzed by comparing the projected traffic volumes on the study segments to their service volumes and adopted LOS standards. The total projected traffic volume is composed of background traffic and project trips. **Table 5** summarizes the roadway segment capacity analysis, which reveals that all roadway segments will continue to operate adequately at project buildout.

Table 5
Projected Roadway Segment Capacity Analysis

Roadway Segment	Seg ID	No Lns	LOS Std	PH Dir Capacity	Dir	Exist Vol	Growt h Rate	2024 Backg'd	Trip Distr	Proj Dir	Project Volume	Total Volume	LOS
SR 19													
CR 561 to Lake Harris North End	NA	4	D	1,190	NB SB	657 805	4.24%	796 976	25%	OUT IN	55 93	851 1,069	D D
Lake Harris North End to CR 48	NA	2	D	1,200	NB SB	657 805	4.24%	796 976	25%	OUT IN	55 93	851 1,069	D D
CR 48 to Central Ave	NA	2	D	800	NB SB	432 436	3.29%	503 508	45%	OUT IN	99 167	602 675	C C
Central Ave to Taylor Memorial Cemetery	NA	2	D	800	NB SB	432 436	3.29%	503 508	45%	OUT IN	99 167	602 675	C C
Taylor Memorial Cemetery to CR 455 (1)	NA	2	C	900	NB SB	508 503	8.65%	728 721	46%	OUT IN	101 171	829 892	C C
CR 455 to US 27/SR 25 (1)	NA	2	C	900	NB SB	526 541	8.65%	753 775	35%	IN OUT	130 77	883 852	C C
CR 48 (2)													
US 27 to Lime Ave	16	2	D	792	EB WB	366 483	5.62%	469 619	25%	IN OUT	93 55	562 674	C C
Lime Ave to SR 19	16	2	D	792	EB WB	366 483	5.62%	469 619	20%	IN OUT	74 44	543 663	C C
Orange Blossom Rd (2)													
Revels Rd to SR 19	NA	2	D	612	EB WB	8 13	2.00%	9 14	33%	OUT IN	72 123	81 137	C C
Number 2 Rd (2)													
Blue Sink Rd to Mare Ave	NA	2	D	612	EB WB	59 50	2.00%	65 55	5%	OUT IN	11 19	76 74	C C
Central Ave (2)													
Mare Ave to SR 19	NA	2	D	612	EB WB	59 50	2.00%	65 55	28%	OUT IN	61 104	126 159	C C
CR 561													
South Astatula City Limit to CR 455	16	2	D	720	EB WB	520 534	5.33%	659 676	10%	IN OUT	37 22	696 698	D D

Source: 2018 Lake County Annual Traffic Counts

(1) FDOT QLOS HIGHPLAN Analysis for these segments of SR 19

(2) Volumes Obtained from PM Peak Turning Movement Counts

4.3 Intersection Capacity Analysis



The projected volumes for the intersection capacity and operations analysis were calculated by assigning the project trips to the project driveways and adding those volumes to the background volumes at the study intersections. Projected background traffic was estimated using the annual growth rate discussed in the previous section.

The projected AM and PM peak hour volumes are illustrated in **Figures 5 & 6**, respectively. The results of the analysis are summarized in **Table 6**, the analysis worksheets and the intersection volume projection sheets are included in **Appendix I**.

Table 6
Projected Intersection Capacity Analysis

Intersection	Traffic Control	Time Period	EB		WB		NB		SB		Overall	
			Delay	LOS	Delay	LOS	Delay	LOS	Delay	LOS	Delay	LOS
SR 19 & CR 48	Signal	AM	--	--	152.1	F	22.3	C	12.6	B	87.6	F
		PM	--	--	406.9	F	21.7	C	12.3	B	258.8	F
SR 19 & CR 48 (with Improvements)	Signal	AM	--	--	34.3	C	39.6	D	25.3	C	31.9	C
		PM	--	--	44.8	D	40.6	D	40.9	D	43.3	D
SR 19 & Central Ave	TWSC	AM	119.9	F	36.6	E	9.4	A	9.7	A	--	--
		PM	365.2	F	72.0	F	10.9	B	9.6	A	--	--
SR 19 & Florida Ave	TWSC	AM	8.6	A	8.8	A	30.8	D	19.1	C	--	--
		PM	9.0	A	8.9	A	28.3	D	22.2	C	--	--
SR 19 & Orange Blossom Rd	TWSC	AM	50.7	F	--	--	9.3	A	--	--	--	--
		PM	106.0	F	--	--	10.2	B	--	--	--	--
SR 19 & Orange Blossom Rd (with Improvements)	TWSC	AM	19.4	C	--	--	9.3	A	--	--	--	--
		PM	21.2	C	--	--	10.2	B	--	--	--	--
SR 19 & CR 455	TWSC	AM	--	--	183.0	F	--	--	9.9	A	--	--
		PM	--	--	405.1	F	--	--	11.1	B	--	--
US 27 & Florida Turnpike Ramps	Signal	AM	85.3	F	87.6	F	112.3	F	33.0	D	84.8	F
		PM	132.2	F	65.5	E	69.8	E	46.0	D	89.0	F
US 27 & Florida Turnpike Ramps (with Improvements)	Signal	AM	51.3	D	68.7	E	71.0	E	40.2	D	59.1	E
		PM	75.2	E	85.9	F	81.5	F	52.1	D	74.6	E
SR 19 Ramps & US 27	TWSC	AM	12.9	B	38.1	E	--	--	38.1	E	--	--
		PM	13.9	B	0.0	A	--	--	47.6	E	--	--
Number 2 Road & Project Access #1	TWSC	AM	--	--	7.4	A	9.2	A	--	--	--	--
		PM	--	--	7.6	A	9.4	A	--	--	--	--
SR 19 & Project Access #2 (Main Entrance)	TWSC	AM	17.0	C	--	--	8.9	A	--	--	--	--
		PM	18.6	C	--	--	9.9	A	--	--	--	--
Orange Blossom Rd & Project Access #3	TWSC	AM	--	--	--	--	--	--	9.3	A	--	--
		PM	--	--	--	--	--	--	9.4	A	--	--

The analysis reveals that the intersection of SR 19 & CR 48, and the minor street of the intersection of SR 19 at Central Avenue, CR 455 and Orange Blossom Road are projected to operate inadequately at the project buildout due to heavy projected background traffic. Likewise, the intersection of US 27 and Florida Turnpike ramps is projected to operate inadequately at the project buildout. The remaining study intersections will operate adequately at project buildout.



Legend:
Background + (Project) = Total

In order to improve the operation of both signalized intersections of SR 18 & CR 48 and US 27 & Florida Turnpike ramps, it is recommended to modify the signal timing and phasing plans for both signals. The improved LOS for both signals is presented in Table 6. As for the 2-Way Stop controlled intersections of SR 19 and Central and SR 19 and CR 455, both intersections will be failing based on background traffic growth in the area and both intersections should be monitored in the future for a possible signal warrant. Finally, the intersection of SR 19 and Orange Blossom Road should be improved by the addition of a northbound left turn lane and a southbound right turn lane. This improvement will be warranted by the proposed development as Phase 2 of the project starts, because the project access for Phase 2 will be via Orange Blossom Road. The improved LOS for this intersection is also presented in Table 6.

5.0 ACCESS REVIEW

The development will be accessed via proposed access point on SR 19, Number 2 Road and Orange Blossom Road. The proposed project access #1 will provide access the north end of the project from Number 2 Road, which is Phase 3. Access #2 will be the main entrance to the development on SR 19 (Phase 1), while Access #3 will access the south end of the project from Orange Blossom Road (Phase 2).

5.1 Turn Lane Review

Right Turn Deceleration Lane at Project Driveways

A right turn deceleration lane warrant was conducted for each of the proposed project access driveways based on the *NCHRP Report 457* Methodology. The results of the right turn warrant analysis show that a right turn deceleration lane is warranted at proposed project Access #2 on SR 19. The dimension of the northbound right turn lane is calculated based on the requirements of *FDOT Design Manual Exhibit FDM 212.1*, included in **Appendix L**, which shows a deceleration length of 405 feet for a design speed of 60 mph. Therefore, the recommended southbound right turn deceleration lanes on SR 19 at the project access #2 is 405 feet (including a 50-foot taper). The right turn lane warrant analyses sheets are included in **Appendix M** for all three access driveways.

Left Turn Deceleration Lane at Project Driveways

Based on the *NCHRP Report 457* Methodology, a left turn deceleration lane is only warranted on SR 19 at the project access #2 (the main project entrance). Based on roadway posted speed limit of 55mph, the required length of the left turn lane is calculated as follows:

Left Turn Lane = Deceleration + Queue Storage

Deceleration @ 60 mph design speed = 405 feet (using FDM Exhibit 212-1)

Queue length = $2 \times 25 \times \text{Left Turn Volume (67 veh)}/60 = 56$ feet (use 60 feet)

Left Turn Lane = 405+ 60 = 465 feet (including a 50-foot taper)

Therefore, the approach will be provided with 465 ft northbound left turn deceleration lane. The left turn lane warrant analyses sheets are included in **Appendix M** for all three access driveways.

6.0 STUDY CONCLUSIONS

This traffic analysis was conducted to assess the impact of the proposed development of Mission Rise in the Town of Howey-in-the-Hills, Lake County, Florida. The project is a residential community with 629 single family units to be built in three phases. The analysis included a determination of project trip generation, a review of existing and projected roadway and intersection capacity, and access review.

The results of the traffic analysis are summarized as follows:

- The proposed development will generate 5,648 trips per day, of which 453 trips will occur during the AM peak hour and 591 trips will occur during the PM peak hour.
- The analysis indicates that the roadway segments currently operate adequately within their Level of Service (LOS) standard and will continue to do so at the buildout of the project.
- The intersections of SR 19 & CR 48 and US 27 & Florida Turnpike Ramps will require modifications to the signal timing and phasing plans in order to operate adequately.
- The 2-Way Stop controlled intersections of SR 19 and Central and SR 19 and CR 455 should be monitored in the future for a possible signal warrant.
- The intersection of SR 19 and Orange Blossom Road should be improved by the addition of a northbound left turn lane and a southbound right turn lane. This improvement will be warranted by the proposed development at the start of Phase 2 of the project.
- A southbound right turn lane and northbound left turn lane are warranted at the intersection of SR 19 and project access #2 (main entrance). The study recommends 405 feet and 465 feet for the southbound right turn lane and northbound left turn lane, respectively.

APPENDICES

Appendix A
Study Methodology &
LSMPO Comments



MEMORANDUM

January 28, 2019

Re: MISSION RISE
Traffic Impact Analysis Methodology
Project № 19011

The following is a methodology outline for the Traffic Impact Analysis (TIA) for the above referenced project. The methodology is consistent with the requirements of Lake County and the Lake-Sumter Metropolitan Planning Organization (LSMPO) for a Tier 2 TIA.

Project Description

The proposed project is a residential community of 629 single family dwelling units with anticipated buildout in 2024. A copy of the proposed site plan is provided in the **Attachments**.

Project Location

The +/- 241-acre site is located west of SR 19, south of Number Two Road and approximately 1.3 miles north of CR 455 in the town of Howey in the Hills, Lake County, Florida, as shown in **Figure 1**.




Figure 1 – Project Location

Project Access

Access to the site is proposed via four (4) full accesses driveway on these roadways:

- SR 19
- Revels Rd
- Number Two Road
- Orange Blossom Road

Trip Generation

The trip generation analysis was conducted using information published by the Institute of Transportation Engineers (ITE) in the *Trip Generation Manual, 10th Edition*. **Table 1** summarizes the trip generation analysis, and the detailed ITE sheets are included in the **Attachments**.

Table 1
Trip Generation

ITE Code	Land Use	Size	Daily		AM Peak Hour				PM Peak Hour			
			Rate	Trips	Rate	Total	Enter	Exit	Rate	Total	Enter	Exit
210	Single Family	629 DU	8.98	5,648	0.72	453	113	340	0.94	591	372	219

Trip Generation analysis based on ITE Trip Generation Manual, 10th Edition.

The development is projected to generate more than 100 net new peak hour trips and therefore a Tier 2 Traffic Impact Analysis is required.

Trip Distribution

The travel demand model based on the Florida Standard Transportation Model Structure (FSUTMS) was used to generate a general distribution pattern for the development. The model output is included in the **Attachments**. The proposed trip distribution pattern presents as follows:

To/from North (SR 19)	25%
To/from South (SR 19)	35%
To/from East (CR 455)	15%
To/from West (CR 48)	25%

Study Area

In accordance with the requirements of Tier 2 TIA methodology, the study area will encompass significance roadway segments and intersections within 4.55-mile radius in addition to roadways where development is expected to consume 5% or more of their adopted Level of Service (LOS) capacities.

Table 2
Study Area

Road Name	From	To	#LNS	AT	LOS STD	LOS CAP	Project Trips			% Cap	Within 4.55 mi.?	In Study?
							% Dist	NB/EB	SB/WB			
SR 19	Savage Ct	CR 48	2	T	C	850	21%	78	46	9.2%	YES	YES
	CR 48	W Central Ave	2	T	C	710	45%	99	167	23.5%	YES	YES
	W Central Ave	Revels Rd	2	T	C	850	48%	105	179	21.1%	YES	YES
	Revels Rd	Orange Blossom Rd	2	T	C	850	52%	114	193	22.7%	YES	YES
	Orange Blossom Rd	E Dewey Robbins Rd	2	T	C	850	50%	110	186	21.9%	YES	YES
	E Dewey Robbins Rd	CR 455	2	T	C	850	50%	110	186	21.9%	YES	YES
CR 48	Bella Vista Blvd	SR 19	2	T	D	720	23%	50	86	11.9%	YES	YES
Orange Blossom Rd	Revels Rd	SR 19	2	T	D	612	23%	50	86	14.1%	YES	YES
Number Two Rd	Blue Sink Rd	Mare Ave	2	T	D	612	26%	57	97	15.8%	YES	YES
W Central Ave	Mare Ave	SR 19	2	T	D	612	26%	57	97	15.8%	YES	YES
	SR 19	Lakeshore Blvd	2	T	D	612	3%	7	11	1.8%	YES	NO
Revels Rd	SR 19	Lakeshore Blvd	2	T	D	612	22%	48	82	13.4%	YES	YES
CR 455	CR 561	SR 19	2	T	D	1,200	15%	56	33	4.7%	YES	NO

Source: 2015 Lake County TCMS Segment Report 01-16-2015

The following roadway segments and intersections will be analyzed for the PM peak hour as part of this study:

Roadway Segments

- SR 19
 - CR 48 to W Central Avenue
 - Central Avenue to Revels Road
 - Revels Road to Orange Blossom Road
 - Orange Blossom Road to E. Dewey Robbins Road
 - E. Dewey Robbins Road to CR 455
- CR 48
 - Bella Vista Boulevard to SR 19
- Orange Blossom Road
 - Chris Road to Revels Road
 - Revels Road to SR 19
- Number Two Road
 - Blue Sink Road to Mare Avenue
- Central Avenue
 - Mare Avenue to SR 19

- Revels Road
 - SR 19 to Lakeshore Boulevard

The following intersections will be analyzed for the AM and PM peak hour:

Study Intersections

- SR 19 and Revels Rd (Unsignalized)
- SR 19 and CR 48 (Signalized)
- SR 19 and Central Avenue (Unsignalized)
- SR 19 and Orange Blossom Road (Unsignalized)
- Site Access driveway No. 1 at SR 19 (Proposed)
- Site Access driveway No. 2 at Orange Blossom Road (Proposed)
- Site Access driveway No. 3 at Number Two Road (Proposed)
- Site Access driveway No. 1 at Revels Road (Proposed)

Capacity Analysis

The TIA will include an analysis of the peak hour conditions in the existing year and the project buildout year (2024). The capacity analysis will be based on service volumes from the *FDOT's 2013 Quality/Level of Service (Q/LOS) Manual* and the methods of the *Highway Capacity Manual* (HCM 6th Edition). Roadway conditions will be analyzed for the PM peak conditions while intersections will be analyzed for the AM and PM peak hour conditions.

Projected Traffic

The TIA will include an analysis of the roadway segments in the PM peak hour. The study intersections will be analyzed for both AM and PM peak hour operations. Offsite and access improvements necessary to support the proposed development at buildout will be identified in the study. The capacity analysis will be based on service volumes from *FDOT's 2013 Quality/Level of Service (Q/LOS) Manual* and the methods of *Highway Capacity Manual* (HCM 6th Edition).

Projected background traffic for the buildout year (2024) will be calculated using a 5-year historical annual growth rate or a minimum annual growth rate of 2.0% and/or committed trips generated by approved developments within the study area if applicable. Historical traffic volume counts will be obtained from Lake County or FDOT to determine the observed traffic growth on the study segments. Up to 5 years of historical traffic data will be analyzed to obtain the observed regional annual growth rate.

Planned and Programmed Improvements

Planned and programmed improvements that may be available from the County's Capital Improvement Program (CIP), the FDOT's Work Program, and/or the LSMPO Transportation Improvement Program (TIP) for any of the study segments will be utilized, if applicable.

Report

A report will be prepared for submittal to Lake County and LSMPO documenting the analysis and findings.



February 6, 2019

Dairian Burke
Town Clerk/Finance Director
Town of Howey-in-the-Hills
101 N. Palm Avenue
PO Box 128
Howey-in-the-Hills, FL 34737

RE: Mission Rise Methodology for a Tier 2 Traffic Impact Analysis (TIA)

Mr. Burke,

The Lake~Sumter MPO has reviewed the documents submitted for the Mission Rise Methodology for a Tier 2 Traffic Impact Analysis (TIA) dated January 28, 2019. The Lake~Sumter MPO offers the following Comments:

Comments Regarding the Project:

1. The project site is located on the west side of SR 19, at the intersection of Revels Road, in the Town of Howey-in-the-Hills, Lake County, Florida.
2. The applicant is proposing to construct 629 single family residential dwelling units on approximately 241 acres of vacant land.
3. The proposed buildout year is 2024.
4. There are four (4) access points proposed for the project as follows:
 - The primary access will be provided via a driveway onto SR 19 just south of Revels Road.
 - One driveway onto Revels Road (currently a dirt road).
 - One driveway onto Number 2 Road (narrow paved road with no center line).
 - One driveway onto Orange Blossom Road (narrow paved road with no center line).Please provide a map or site plan that clearly shows the access points.
5. The trip generation for this development as shown in Table 1 uses the ITE Equations. When the equations are used, please show the inputs and calculations (either in the text of the document or in the appendix) so that non-transportation professionals can understand how the trip generation rates and volumes were derived.
6. The trip generation shows the proposed development would have approximately 5,648 daily trips, 453 AM Peak Hour Trips, and 591 PM Peak Hour Trips.
7. A study area distance of 4.55 miles, and where the project trips are 5% of the adopted Level of Service (LOS), is acceptable. However, when showing the roadway segments (Table 2), show the next roadway segment that has project trips that are less than 5% of LOS capacity (show where the project impact ends).
8. For the Roadway segment to study, at a minimum, please include:
 - SR 19 from Savage Ct. to CR 48 (as identified in Table 2).
 - SR 19 from CR 455 to US 27.

"Promoting Regional Transportation Partnerships"

www.LakeSumterMPO.com

225 W. Guava St. Suite 211, Lady Lake, Florida 32159
Phone (352) 315-0170

9. Please add the following intersections to the study:
 - SR 19 at Florida Ave.
 - SR 19 at CR 455.
 - SR 19 at Florida's Turnpike.
 - US 27 at Turnpike Ramps/SR 19.
10. Please provide a map showing the study area roadway segments and intersections to be studied.
11. It is proposed that both the AM and PM Peak Hours will be analyzed. This is acceptable.
12. The future traffic conditions will use a growth rate calculated from historical traffic counts with a minimum 2% growth. This is acceptable. Please be sure to use the latest available traffic counts from Lake County and the FDOT.
13. The Lake~Sumter MPO reserves the right to provide additional recommendations which may include expanding the scope of the analysis based on the results of the initial TIA.
14. Please include the Recommended Multimodal Accommodations listed below when developing the project site plan.

Recommended Multimodal Accommodations:

1. Provide continuous pedestrian facilities along all major streets; these should be direct and interconnect with all other modes of transportation within the project and onto adjacent properties.
2. Require the developer to provide ramps and curb cuts throughout the pedestrian system for physically challenged persons.

Should you have any questions please contact me by email at bhutt@lakesumtermpo.com or by phone at (352) 315-0170 ext. 3.

Thank You,

Brian R. Hutt

Brian R. Hutt, AICP
Lake~Sumter MPO
TMS Project Manager

Appendix B
Preliminary Development Plan



HANOVER
Land Company, LLC

MISSION RISE

HOWEY-IN-THE-HILLS

60' LOTS [219]

50' LOTS [183]

40' LOTS [227]


Total Lots - 629

TRAIL NETWORK

- 1 - SECONDARY ENTRY OFF NUMBER 2 ROAD
- 2 - WETLAND PROTECTION AREA
- 3 - AMENITY AREA WITH POOL AND TOT LOT
- 4 - MAIN ENTRY OFF SR-19

OPEN SPACE TOTALS BY LAND USE

WETLANDS	30.16 AC
DRY RETENTION	32.29 AC
NON-PARK OPEN SPACE	9.38 AC
PARK	10.28 AC
AMENITIES	.25 AC
TOTAL	82.36 AC



Appendix C
2018 Lake County TMS & FDOT High-plan Service Volume

2018 Lake County Annual Traffic Counts

MAP STA #	ROAD NAME	LOCATION	Map Sheet	TMS ID	S E C	T W P	R N G	ANNUAL ADJUSTED DAILY TRAFFIC (AADT)					5-YEAR ANNUAL AVERAGE GROWTH RATE PERCENT
								2014	2015	2016	2017	2018	
16 C.R. 48		0.25 MI E OF U.S. 27	B	97	14	20	24	8,765	6,895	9,996	10,428	10,908	5.62%
17 C.R. 48		0.18 MI E OF C.R. 33	B	219	15	20	24	4,978	6,580	11,043	8,307	8,867	15.53%
18 C.R. 48		0.12 MI W OF C.R. 33	B	224	22	20	24	2,221	2,019	3,559	3,520	3,145	9.08%
34 C.R. 48		0.18 MI W OF S.R. 19	B	99	23	20	25	7,252	8,181	8,304	9,300	9,304	6.43%
59 C.R. 48		0.15 MI E OF C.R. 561	B	356	32	20	26	5,448	7,855	5,857	5,977	6,305	3.72%
153 C.R. 48		0.12 MI W OF U.S. 27	B	218	14	20	24	6,733	8,459	7,698	8,996	9,714	9.60%
68 C.R. 50		0.05 MI W OF PARK TRAIL DR	B	158	17	22	26	10,129	9,478	7,238	8,979	8,482	-4.34%
69 C.R. 50		0.06 MI W OF ORANGE CO LINE	A	155	25	22	26	6,100	5,051	5,950	7,322	7,060	3.72%
158 C.R. 50		0.08 MI W OF C.R. 455	B	156	23	22	26	4,308	6,698	5,592	7,593	6,893	11.64%
275 C.R. 50/SUNSET AV		0.03 MI N OF S.R. 50	B	161	14	22	24	1,144	1,224	1,810	1,342	1,486	6.23%
37 C.R. 561		0.16 MI S OF BRIDGE #114046	B	781	23	22	25	2,886	3,073	3,272	3,564	3,579	5.52%
55 C.R. 561		0.26 MI S OF S.R. 19	C	613	6	20	26	10,380	10,585	12,230	13,334	14,040	7.84%
57 C.R. 561		0.07 MI S OF WOODLAND DR	B	118	20	20	26	7,393	8,032	8,017	8,000	9,245	5.75%
60 C.R. 561		0.55 MI S OF C.R. 48	B	719	32	20	26	8,772	9,150	9,404	10,141	10,798	5.33%
61 C.R. 561		0.13 MI S OF C.R. 455	B	121	17	21	26	6,147	6,213	5,548	6,639	7,090	3.63%
63 C.R. 561		0.04 MI N OF C.R. 561A	B	0	30	21	26	6,289	6,582	6,492	7,281	10,671	14.13%
102 C.R. 561		0.08 MI S OF C.R. 565/BLOG HOUSE	A	128	11	23	25	2,557	4,585	2,094	2,340	3,399	7.37%
139 C.R. 561		0.11 MI E OF S.R. 33	A	131	8	24	25	1,231	1,483	1,467	2,050	2,002	12.93%
176 C.R. 561		0.08 MI S OF C.R. 565A	B	720	24	22	25	5,515	5,871	6,142	6,165	6,728	5.10%
207 C.R. 561		0.10 MI N OF C.R. 565A	B	605	14	22	25	4,173	5,073	4,391	5,294	5,863	8.87%
66 C.R. 561 (LAKE MINNEOLA SHIP)		0.11 MI W OF U.S. 27	B	602	7	22	26	7,561	8,743	9,426	8,727	9,602	6.15%
32 C.R. 561/C.R. 561A		0.09 MI E OF U.S. 27	B	125	36	21	25	7,664	8,680	10,449	9,629	9,788	6.31%
62 C.R. 561A		0.18 MI E OF C.R. 561	B	596	30	21	26	1,397	1,544	1,531	1,676	4,669	35.21%
64 C.R. 561A		0.35 MI E OF SCRUB JAY RD	B	596	32	21	26	1,378	1,570	1,381	1,773	6,227	45.81%
35 C.R. 565		0.07 MI S OF U.S. 27	B	610	18	21	25	978	1,189	1,277	1,588	1,981	19.31%
206 C.R. 565 (VILLA CITY RD)		0.134 MI N OF S.R. 50	B	612	24	22	24	2,838	3,744	3,180	3,359	4,422	11.72%
136 C.R. 565A		0.2 MI N OF S.R. 50	B	599	20	22	25	7,386	9,936	10,992	8,120	9,069	5.27%
137 C.R. 565A		0.27 MI S OF S.R. 50	A	594	20	22	25	1,965	3,541	2,186	2,213	2,149	2.27%
138 C.R. 565B		0.10 MI E OF C.R. 565A	A	593	3	23	25	2,055	2,194	2,173	2,511	2,433	4.31%
227 CANAL ST		0.026 MI N OF MAIN ST	C	663	26	19	24	3,913	5,849	4,776	4,335	4,188	1.71%
228 CANAL ST		0.035 MI S OF MAIN ST	C	663	26	19	24	3,183	5,107	3,361	3,417	3,312	1.00%
309 CHULA VISTA AV		BETWEEN RIO & SAN REMO	B	159	18	18	24	*****	2,503	2,678	3,805	3,249	
195 CITRUS GROVE ROAD		0.14 MI E OF U.S. 27	B	546	6	22	26	904	1,009	1,385	1,612	1,847	19.57%
169 CITRUS TOWER BV		0.14 MI N OF S.R. 50	A	833	28	22	26	17,147	15,715	16,110	15,791	15,478	-2.53%
178 CITRUS TOWER BV		0.113 MI E OF U.S. 27	B	135	19	22	26	11,752	12,303	12,177	12,067	12,548	1.66%
197 CITRUS TOWER BV		0.10 MI N OF JOHNS LAKE RD	A	884	32	22	26	14,849	17,884	18,431	18,370	19,580	7.16%
280 CITRUS TOWER BV		0.1 MI S OF S.R. 50	A	146	28	22	26	15,687	17,410	17,355	17,358	18,604	4.36%
283 CITRUS TOWER BV		0.18 E. OF U.S. 27	A	910	5	23	26	12,393	14,550	14,579	14,720	15,036	4.95%
288 CR 44A		0.17 MI N. OF CR 44A	C-1	823	5	19	27	1,817	1,945	1,935	2,092	2,171	4.54%
291 CR 48		AT SUMTER COUNTY LINE	B	225	7	21	24	2,218	1,429	2,778	2,912	2,849	6.46%
293 CR 50		EAST OF HANCOCK RD	B	157	16	22	26	9,591	6,847	9,026	11,238	10,448	2.16%
292 CR 561A		WEST OF CR 455	B	132	27	21	26	1,496	1,675	1,579	1,583	1,940	6.72%
315 CR 565A		NORTH OF SR 50	C	494	24	22	24	*****	469	363	582	4,343	
307 CR46A		SOUTH OF SR44	B	157	8	19	28	*****	7,237	8,047	9,046	8,995	
156 DAVID WALKER DR		0.05 MI N OF U.S. 441/S.R. 500	C-1	424	22	19	26	4,363	5,239	5,459	5,928	7,235	13.48%
157 DAVID WALKER DR		0.05 MI W OF KURT ST (EUSTIS)	C-1	721	15	19	26	4,562	4,724	5,651	5,099	5,205	3.35%
168 DAVID WALKER DR		0.20 MI S OF U.S. 441	C-1	423	22	19	26	6,860	7,505	7,612	7,672	8,369	5.09%
234 DEAD RIVER RD		0.2 MI W OF S.R. 19	C-1	589	31	19	26	6,284	6,821	7,205	7,484	7,830	2.10%
305 DEWEY ROBBINS RD		EAST OF US27	B	0	36	20	24	*****	380	448	500	609	

ADJUSTED PEAK HR VOLUME 2018	BEGIN PEAK HOUR 2018	ADJUSTED P.M. PEAK HOUR VOLUME 2018 (3-7 pm reported as 15:00-19:00)				
		Total	NB/EB	SB/WB	Pk Dir	Time
948	15:30	948	373	576	WB	15:30
720	15:30	720	336	384	WB	15:30
281	16:30	281	91	190	WB	16:30
757	16:30	757	367	390	WB	16:30
800	7:45	595	288	307	WB	16:45
788	10:30	738	365	372	WB	16:00
791	7:30	761	322	439	WB	16:30
770	17:00	770	224	546	WB	17:00
716	17:15	716	491	225	EB	17:15
153	16:45	153	68	86	SB	16:45
323	16:15	323	169	154	NB	16:15
1,165	16:30	1,165	548	616	SB	16:30
813	16:30	813	364	449	SB	16:30
1,053	16:30	1,053	520	534	SB	16:30
688	16:45	688	332	357	SB	16:45
1,060	16:30	1,060	518	542	SB	16:30
663	7:45	447	266	181	NB	15:00
201	16:30	201	114	86	NB	16:30
635	16:45	635	307	327	SB	16:45
511	7:30	492	221	271	SB	16:45
828	7:30	803	345	458	WB	17:00
868	16:45	868	420	448	WB	16:45
456	6:45	448	199	248	WB	16:15
612	6:45	599	330	269	EB	16:30
196	7:15	186	177	9	NB	17:00
373	17:00	373	192	181	NB	17:00
1,006	6:45	699	375	324	NB	17:15
199	16:45	199	122	77	NB	16:45
230	15:30	230	115	114	EB	15:30
348	16:45	348	180	168	NB	16:45
272	14:30	266	154	112	NB	15:00
385	14:15	346	153	193	SB	15:00
198	6:45	160	57	103	WB	17:15
1,254	14:30	1,226	579	647	SB	16:15
1,102	16:30	1,102	483	619	WB	16:30
1,588	17:45	1,588	604	984	SB	17:45
1,482	16:30	1,482	832	650	NB	16:30
1,201	7:15	1,162	459	703	WB	16:30
190	15:30	190	106	84	NB	15:30
257	16:45	257	80	177	SB	16:45
979	16:30	979	474	505	WB	16:30
219	6:45	189	112	76	EB	16:30
379	15:30	379	192	187	NB	15:30
762	15:00	762	472	290	NB	15:00
597	11:00	544	342	202	NB	16:45
511	16:30	511	323	188	EB	16:30
679	14:15	672	370	302	EB	16:30
564	17:00	564	233	331	WB	17:00
63	15:30	63	36	27	EB	15:30

HIGHPLAN 2012 Conceptual Planning Analysis

Project Information

Analyst	TMC	Highway Name	SR 19	Study Period	Standard K
Date Prepared	2/13/2019 2:56:39 PM	From	Taylor Memorial Cemetery	Analysis Type	Two-Lane Segment
Agency	Lake Co	To	US 27	Program	HIGHPLAN 2012
Area Type	Transitioning/Urban	Peak Direction	Northbound	Version Date	12/12/2012
File Name	T:\AProjectFiles\2019\19011 Mission Rise\TIA\Highplan Service volume\Highplan SR 19 CR 455 to US 27.xhp				
User Notes					

Highway Data

Roadway Variables				Traffic Variables			
Segment Length	4.800	Median	No	AADT	11800	PHF	0.970
# Thru Lanes	2	Left Turn Impact	No	K	0.090	% Heavy Vehicles	10.0
Terrain	Level	Pass Lane Length	N/A	D	0.545	Base Capacity	1700
Posted Speed	55	% NPZ	43	Peak Dir. Hrly. Vol.	579	Local Adj. Factor	0.95
Free Flow Speed	60	Class	3	Off Peak Dir. Hrly. Vol.	483	Adjusted Capacity	1615

LOS Results

v/c Ratio	0.37	Density	N/A	PTSF	75.1	ATS	49.3	% FFS	82.2
FFS Delay	62.2	LOS Thresh. Delay	4.6	Service Measure	PctFFS	LOS	C		

Service Volumes

Note: The maximum normally acceptable directional service volume for LOS E in Florida for this facility type and area type is 1650 veh/h/ln.

	A	B	C	D	E
Lanes	Hourly Volume In Peak Direction				
1	150	520	900	1240	1560
2					
3					
4					
Lanes	Hourly Volume In Both Directions				
2	280	960	1660	2280	2870
4					
6					
8					
Lanes	Annual Average Daily Traffic				
2	3200	10700	18500	25400	31900
4					
6					
8					

* Cannot be achieved based on input data provided.

Performance measure results are no longer applicable with the presence of passing lanes. Refer to the service volume tables to obtain the LOS.


Appendix D
Turning Movement Counts & Seasonal Factor Data

TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): SR 19
Intersection (E/W): CR 48

Date: 1/23/2019

SR 19				SR 19			CR 48			CR 48			TOTAL
Start	End	NB		SB		R	EB		WB		R		
		L	T	L	T		L	T	L	T			
7:00 AM	7:15 AM	0	22	88	54	19	0	0	0	50	0	42	275
7:15 AM	7:30 AM	0	23	86	55	19	0	0	0	75	0	85	343
7:30 AM	7:45 AM	0	27	98	91	23	0	0	0	96	0	60	395
7:45 AM	8:00 AM	0	21	81	63	23	0	0	0	75	0	58	321
8:00 AM	8:15 AM	0	19	75	80	22	0	0	0	72	0	41	309
8:15 AM	8:30 AM	0	19	81	63	10	0	0	0	66	0	67	306
8:30 AM	8:45 AM	0	20	70	60	15	0	0	0	58	0	54	277
8:45 AM	9:00 AM	0	21	63	63	12	0	0	0	51	0	60	270
Total for:		7:00 AM	8:00 AM		263	84	0	0	0	296	0	245	1334
Total for:		8:00 AM	9:00 AM		266	59	0	0	0	247	0	222	1162
Total Peak Hour:		7:15 AM	8:15 AM		289	87	0	0	0	318	0	244	1368
Overall PHF:		0.87											




TURNING MOVEMENT COUNT ANALYSIS

AUTOS & TRUCKS

Intersection (N/S): SR 19
Intersection (E/W): CR 48

Date: 1/23/2019

SR 19				SR 19				CR 48				CR 48				TOTAL
Start	End	NB		SB		R	EB		WB		R					
		L	T	L	T		L	T	L	T						
4:00 PM	4:15 PM	0	21	80	53	24	0	0	0	0	97	0	57	332		
4:15 PM	4:30 PM	0	14	66	93	25	0	0	0	0	84	0	56	338		
4:30 PM	4:45 PM	0	18	71	90	31	0	0	0	0	96	0	60	366		
4:45 PM	5:00 PM	0	19	82	67	12	0	0	0	0	113	0	68	361		
5:00 PM	5:15 PM	0	20	76	99	21	0	0	0	0	85	0	100	401		
5:15 PM	5:30 PM	0	20	103	64	15	0	0	0	0	121	0	107	430		
5:30 PM	5:45 PM	0	20	88	70	18	0	0	0	0	100	0	102	398		
5:45 PM	6:00 PM	0	18	91	66	13	0	0	0	0	94	0	96	378		
Total for:		4:00 PM	5:00 PM		303	92	0	0	0	0	390	0	241	1397		
Total for:		5:00 PM	6:00 PM		299	67	0	0	0	0	400	0	405	1607		
Total Peak Hour:		5:00 PM	6:00 PM		299	67	0	0	0	0	400	0	405	1607		
Overall PHF:		0.93														



Intersection (N/S): SR 19
Intersection (E/W): W. Central Ave
Date: 1/23/2019

Peak Hour Volumes

Southbound

19

355

SR 19

19

W. Central Ave

Northbound

16

358

SR 19

13

W. Central Ave

Eastbound

25

8

9

Westbound

7

8

10

Intersection (N/S): SR 19
Intersection (E/W): W. Central Ave
Date: 1/23/2019

Peak Hour Volumes

Direction	Lane	Volume
Southbound	Left	31
	Middle	410
	Right	13
Northbound	Left	9
	Middle	388
	Right	10
Westbound	Left	9
	Middle	10
	Right	12
Eastbound	Left	35
	Middle	10
	Right	14


TURNING MOVEMENT COUNT ANALYSIS

AUTOS & TRUCKS

Intersection (N/S): SR 19
Intersection (E/W): S. Florida Ave
Date: 2/7/2019

Start	End	SR 19			SR 19			S. Florida Ave			S. Florida Ave			TOTAL
		L	T	R	L	T	R	L	T	R	L	T	R	
7:00 AM	7:15 AM	9	90	0	2	90	5	0	0	4	1	0	6	207
7:15 AM	7:30 AM	2	62	3	0	82	0	1	0	5	3	0	6	164
7:30 AM	7:45 AM	5	105	5	0	89	0	0	0	0	7	0	1	212
7:45 AM	8:00 AM	7	87	2	5	91	1	3	3	8	9	2	6	224
8:00 AM	8:15 AM	2	98	1	1	100	0	2	0	11	11	0	8	234
8:15 AM	8:30 AM	4	85	4	2	89	1	1	1	2	6	1	4	200
8:30 AM	8:45 AM	2	79	5	0	75	0	0	0	4	3	2	2	172
8:45 AM	9:00 AM	3	80	3	1	84	2	1	1	4	5	1	3	188

Total for:	7:00 AM	23	344	10	7	352	6	4	3	17	20	2	19	807
Total for:	8:00 AM	11	342	13	4	348	3	4	2	21	25	4	17	794
Total Peak Hour:	7:30 AM	18	375	12	8	369	2	6	4	21	33	3	19	870
Overall PHF:		0.93												




TURNING MOVEMENT COUNT ANALYSIS

AUTOS & TRUCKS

Intersection (N/S): SR 19
 Intersection (E/W): S. Florida Ave
 Date: 2/7/2019

Start	End	NB			SB			EB			WB			TOTAL
		L	T	R	L	T	R	L	T	R	L	T	R	
4:00 PM	4:15 PM	1	93	4	4	138	1	0	2	5	3	1	1	253
4:15 PM	4:30 PM	4	98	3	4	84	0	0	0	3	3	0	3	202
4:30 PM	4:45 PM	2	101	5	5	100	0	1	1	1	2	1	4	223
4:45 PM	5:00 PM	3	99	2	4	96	1	2	1	2	5	0	5	220
5:00 PM	5:15 PM	4	88	2	3	104	0	0	0	5	1	0	2	209
5:15 PM	5:30 PM	6	91	3	6	111	2	1	0	3	4	1	3	231
5:30 PM	5:45 PM	5	85	5	7	97	1	0	1	5	3	0	1	210
5:45 PM	6:00 PM	6	92	4	6	89	1	2	0	3	5	1	3	212

Total for:	4:00 PM	10	391	14	17	418	2	3	4	11	13	2	13	898
Total for:	5:00 PM	21	356	14	22	401	4	3	1	16	13	2	9	862
Total Peak Hour:	4:00 PM	10	391	14	17	418	2	3	4	11	13	2	13	898
Overall PHF:	0.89													



Intersection (N/S): SR 19
Intersection (E/W): Revels Rd
Date: 1/23/2019

Peak Hour Volumes


Direction	Left Turn	Through/Right Turn
Northbound	42	405
Southbound	1	346
Eastbound	0	0
Westbound	9	6

TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): SR 19
Intersection (E/W): Revels Rd
Date: 1/23/2019

Start	End	SR 19			SR 19			Revels Rd			Revels Rd			TOTAL
		L	T	R	L	T	R	L	T	R	L	T	R	
4:00 PM	4:15 PM	0	105	3	1	96	1	1	0	0	2	0	1	210
4:15 PM	4:30 PM	0	82	3	0	108	0	0	0	0	2	0	0	195
4:30 PM	4:45 PM	0	91	2	0	114	0	0	0	0	2	0	0	209
4:45 PM	5:00 PM	0	90	1	2	85	0	0	0	0	2	0	0	180
5:00 PM	5:15 PM	0	93	2	0	101	0	0	0	0	4	0	2	202
5:15 PM	5:30 PM	0	107	4	2	100	0	0	0	0	1	0	0	214
5:30 PM	5:45 PM	0	83	5	1	137	0	0	1	1	0	0	1	229
5:45 PM	6:00 PM	0	77	2	1	86	0	0	0	0	0	0	0	166


Total for:	4:00 PM	0	368	9	3	403	1	1	0	0	8	0	1	794
Total for:	5:00 PM	0	360	13	4	424	0	0	1	1	5	0	3	811
Total Peak Hour:	4:45 PM	0	373	12	5	423	0	0	1	1	7	0	3	825
Overall PHF:		0.90												



TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): SR 19
Intersection (E/W): Orange Blossom Rd
Date: 1/23/2019


		SR 19			SR 19			Orange Blossom Rd			Orange Blossom Rd			TOTAL
		L	T	R	L	T	R	L	T	R	L	T	R	
Start	End	NB			SB			EB			WB			
7:00 AM	7:15 AM	0	80	0	0	78	0	1	0	3	0	0	0	162
7:15 AM	7:30 AM	0	110	0	0	96	0	1	0	3	0	0	0	210
7:30 AM	7:45 AM	1	130	0	0	103	1	3	0	0	0	0	0	238
7:45 AM	8:00 AM	0	106	0	0	82	1	2	0	3	0	0	0	194
8:00 AM	8:15 AM	0	92	0	0	69	1	0	0	3	0	0	0	165
8:15 AM	8:30 AM	1	101	0	0	77	0	0	0	2	0	0	0	181
8:30 AM	8:45 AM	0	70	0	0	72	2	3	0	3	0	0	0	150
8:45 AM	9:00 AM	1	75	0	0	63	1	2	0	2	0	0	0	144
Total for: 7:00 AM		1	426	0	0	359	2	7	0	9	0	0	0	804
Total for: 8:00 AM		2	338	0	0	281	4	5	0	10	0	0	0	640
Total Peak Hour: 7:15 AM		1	438	0	0	350	3	6	0	9	0	0	0	807
Overall PHF:		0.85												



TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): SR 19
Intersection (E/W): Orange Blossom Rd
Date: 1/23/2019

		SR 19			SR 19			Orange Blossom Rd			Orange Blossom Rd			TOTAL
		L	T	R	L	T	R	L	T	R	L	T	R	
Start	End	NB			SB			EB			WB			
4:00 PM	4:15 PM	2	109	0	0	95	2	1	0	2	0	0	0	211
4:15 PM	4:30 PM	0	84	0	0	109	2	0	0	1	0	0	0	196
4:30 PM	4:45 PM	0	91	0	0	113	1	2	0	2	0	0	0	209
4:45 PM	5:00 PM	1	92	0	0	82	1	1	0	1	0	0	0	178
5:00 PM	5:15 PM	1	95	0	0	106	0	0	0	0	0	0	0	202
5:15 PM	5:30 PM	2	110	0	0	98	4	3	0	1	0	0	0	218
5:30 PM	5:45 PM	1	88	0	0	137	3	2	0	0	0	0	0	231
5:45 PM	6:00 PM	2	78	0	0	84	0	0	0	0	0	0	0	164
Total for: 4:00 PM		3	376	0	0	399	6	4	0	6	0	0	0	794
Total for: 5:00 PM		6	371	0	0	425	7	5	0	1	0	0	0	815
Total Peak Hour: 4:45 PM		5	385	0	0	423	8	6	0	2	0	0	0	829
Overall PHF:		0.90												




TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): SR 19

Intersection (E/W): CR 455

Date: 2/7/2019

		SR 19			SR 19			CR 455			CR 455			TOTAL		
Start	End	NB			SB			EB			WB			TOTAL		
		L	T	R	L	T	R	L	T	R	L	T	R	TOTAL		
7:00 AM	7:15 AM	0	54	17	23	94	0	0	0	0	20	0	4	212		
7:15 AM	7:30 AM	0	86	16	17	92	0	0	0	0	15	0	17	243		
7:30 AM	7:45 AM	0	90	19	18	93	0	0	0	0	18	0	15	253		
7:45 AM	8:00 AM	0	88	21	17	95	0	0	0	0	23	0	14	258		
8:00 AM	8:15 AM	0	95	18	12	84	0	0	0	0	22	0	16	247		
8:15 AM	8:30 AM	0	88	11	6	67	0	0	0	0	18	0	7	197		
8:30 AM	8:45 AM	0	80	12	9	70	0	0	0	0	15	0	10	196		
8:45 AM	9:00 AM	0	55	7	12	57	0	0	0	0	11	0	6	148		
Total for: 7:00 AM		0	318	73	75	374	0	0	0	0	76	0	50	966		
Total for: 8:00 AM		0	318	48	39	278	0	0	0	0	66	0	39	788		
Total Peak Hour: 7:15 AM		0	359	74	64	364	0	0	0	0	78	0	62	1001		
Overall PHF:		0.97														




TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): SR 19

Intersection (E/W): CR 455

Date: 2/7/2019

SR 19				SR 19			CR 455			CR 455			TOTAL
Start	End	NB		SB		R	EB		WB		R		
		L	T	L	T		L	T	L	T			
4:00 PM	4:15 PM	0	100	20	9	130	0	0	0	30	0	10	299
4:15 PM	4:30 PM	0	115	16	12	102	0	0	0	17	0	8	270
4:30 PM	4:45 PM	0	123	19	11	110	0	0	0	21	0	9	293
4:45 PM	5:00 PM	0	113	19	10	122	0	0	0	15	0	17	296
5:00 PM	5:15 PM	0	120	15	13	119	0	0	0	17	0	12	296
5:15 PM	5:30 PM	0	90	27	15	108	0	0	0	29	0	19	288
5:30 PM	5:45 PM	0	89	21	17	102	0	0	0	24	0	22	275
5:45 PM	6:00 PM	0	87	19	9	87	0	0	0	26	0	15	243
Total for: 4:00 PM		0	451	74	42	464	0	0	0	83	0	44	1158
Total for: 5:00 PM		0	386	82	54	416	0	0	0	96	0	68	1102
Total Peak Hour: 4:30 PM		0	446	80	49	459	0	0	0	82	0	57	1173
Overall PHF:		0.99											




TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): **Turpike NB Off Ramp**
Intersection (E/W): **US 27**

Date: **2/7/2019**

Start	End	Turpike NB Off Ramp				Turpike NB Off Ramp				US 27				US 27				TOTAL
		L	T	R	L	T	R	L	T	R	L	T	R	L	T	R	TOTAL	
7:00 AM	7:15 AM	9	39	17	24	10	28	57	148	5	3	181	31	3	181	31	552	
7:15 AM	7:30 AM	11	40	25	25	15	33	49	190	10	9	204	40	9	204	40	651	
7:30 AM	7:45 AM	15	36	31	23	18	35	55	189	6	13	199	33	13	199	33	653	
7:45 AM	8:00 AM	10	43	19	21	22	35	62	219	9	11	244	25	11	244	25	720	
8:00 AM	8:15 AM	9	37	21	22	20	31	58	197	5	10	207	29	10	207	29	646	
8:15 AM	8:30 AM	15	41	19	19	13	29	60	175	8	11	216	29	11	216	29	635	
8:30 AM	8:45 AM	13	34	21	21	15	22	57	170	10	13	220	17	13	220	17	613	
8:45 AM	9:00 AM	7	25	22	15	8	17	55	139	4	10	192	20	10	192	20	514	
Total for: 7:00 AM		45	158	92	93	65	131	223	746	30	36	828	129	36	828	129	2576	
Total for: 8:00 AM		44	137	83	77	56	99	230	681	27	44	835	95	44	835	95	2408	
Total Peak Hour: 7:15 AM		45	156	96	91	75	134	224	795	30	43	854	127	43	854	127	2670	
Overall PHF: 0.93																		




TURNING MOVEMENT COUNT ANALYSIS

AUTOS & TRUCKS

Intersection (N/S): Turnpike NB Off ramp
Intersection (E/W): US 27
Date: 6/27/2018

Turnpike NB Off ramp																	Turnpike NB Off ramp						US 27						US 27					
Start	End	NB			SB			EB			WB			TOTAL																				
		L	T	R	L	T	R	L	T	R	L	T	R		L	T	R																	
4:00 PM	4:15 PM	18	8	18	30	37	44	59	178	10	10	144	33	589																				
4:15 PM	4:30 PM	19	12	22	27	45	51	64	201	13	19	170	25	668																				
4:30 PM	4:45 PM	17	10	31	40	51	56	70	199	15	26	159	24	698																				
4:45 PM	5:00 PM	15	15	29	40	50	48	68	224	10	33	175	27	734																				
5:00 PM	5:15 PM	22	9	22	31	47	52	77	196	17	30	210	18	731																				
5:15 PM	5:30 PM	13	13	31	44	39	60	81	183	10	34	202	26	736																				
5:30 PM	5:45 PM	19	18	29	39	51	59	80	180	16	30	188	20	729																				
5:45 PM	6:00 PM	15	15	33	42	47	61	73	183	10	25	170	17	691																				
Total for: 4:00 PM																	Total for: 4:00 PM						Total for: 4:00 PM											
Total for: 5:00 PM																	Total for: 5:00 PM						Total for: 5:00 PM											
Total Peak Hour: 4:45 PM																	Total Peak Hour: 4:45 PM						Total Peak Hour: 4:45 PM											
Overall PHF: 1.00																	Overall PHF: 1.00						Overall PHF: 1.00											




TURNING MOVEMENT COUNT ANALYSIS
AUTOS & TRUCKS

Intersection (N/S): SR 19 Ramp
Intersection (E/W): US 27

Date: 2/7/2019


		SR 19 Ramp						SR 19 Ramp						US 27			US 27			TOTAL
		NB			SB			EB			WB									
Start	End	L	T	R	L	T	R	L	T	R	L	T	R	L	T	R				
7:00 AM	7:15 AM	0	0	0	9	0	40	25	199	0	0	167	20	460						
7:15 AM	7:30 AM	0	0	0	11	0	55	24	228	0	2	195	17	532						
7:30 AM	7:45 AM	0	0	0	10	0	62	31	225	0	0	181	29	538						
7:45 AM	8:00 AM	0	0	0	15	0	48	29	260	0	1	196	35	584						
8:00 AM	8:15 AM	0	0	0	12	0	41	38	215	0	0	225	31	562						
8:15 AM	8:30 AM	0	0	0	17	0	38	33	223	0	2	229	28	570						
8:30 AM	8:45 AM	0	0	0	10	0	45	24	220	0	1	219	23	542						
8:45 AM	9:00 AM	0	0	0	9	0	40	29	230	0	2	193	17	520						
Total for: 7:00 AM		0	0	0	45	0	205	109	912	0	3	739	101	2114						
Total for: 8:00 AM		0	0	0	48	0	164	124	888	0	5	866	99	2194						
Total Peak Hour: 7:45 AM		0	0	0	54	0	172	124	918	0	4	869	117	2258						
Overall PHF: 0.97																				



TURNING MOVEMENT COUNT ANALYSIS AUTOS & TRUCKS

Intersection (N/S): SR 19 Off Ramp
Intersection (E/W): US 27
Date: 2/7/2019

SR 19 Off Ramp				SR 19 Off Ramp				US 27				US 27				TOTAL	
Start	End	NB		SB		EB		WB		TOTAL	L	T	R	L	T	R	TOTAL
		L	T	L	T	L	T	L	T								
4:00 PM	4:15 PM	0	0	0	33	20	209	0	2	155	20	451					
4:15 PM	4:30 PM	0	0	0	27	29	221	0	0	189	40	521					
4:30 PM	4:45 PM	0	0	0	30	33	239	0	1	182	39	535					
4:45 PM	5:00 PM	0	0	0	27	35	257	0	0	210	44	588					
5:00 PM	5:15 PM	0	0	0	24	31	219	0	0	234	39	560					
5:15 PM	5:30 PM	0	0	0	20	26	230	0	1	240	44	578					
5:30 PM	5:45 PM	0	0	0	24	33	217	0	0	214	25	526					
5:45 PM	6:00 PM	0	0	0	26	32	183	0	0	187	24	463					
Total for:		4:00 PM	5:00 PM	0	0	0	117	117	926	0	3	736	143	2095			
Total for:		5:00 PM	6:00 PM	0	0	0	94	122	849	0	1	875	132	2127			
Total Peak Hour:		4:30 PM	5:30 PM	0	0	0	101	125	945	0	2	866	166	2261			
Overall PHF:		0.96															



2017 PEAK SEASON FACTOR CATEGORY REPORT - REPORT TYPE: ALL
 CATEGORY: 1100 LAKE COUNTYWIDE

WEEK	DATES	SF	MOCF: 0.95 PSCF
1	01/01/2017 - 01/07/2017	0.99	1.04
2	01/08/2017 - 01/14/2017	0.99	1.04
3	01/15/2017 - 01/21/2017	1.00	1.05
4	01/22/2017 - 01/28/2017	0.98	1.03
* 5	01/29/2017 - 02/04/2017	0.97	1.02
* 6	02/05/2017 - 02/11/2017	0.96	1.01
* 7	02/12/2017 - 02/18/2017	0.94	0.99
* 8	02/19/2017 - 02/25/2017	0.94	0.99
* 9	02/26/2017 - 03/04/2017	0.94	0.99
* 10	03/05/2017 - 03/11/2017	0.93	0.98
* 11	03/12/2017 - 03/18/2017	0.93	0.98
* 12	03/19/2017 - 03/25/2017	0.93	0.98
* 13	03/26/2017 - 04/01/2017	0.94	0.99
* 14	04/02/2017 - 04/08/2017	0.94	0.99
* 15	04/09/2017 - 04/15/2017	0.95	1.00
* 16	04/16/2017 - 04/22/2017	0.96	1.01
* 17	04/23/2017 - 04/29/2017	0.97	1.02
18	04/30/2017 - 05/06/2017	0.98	1.03
19	05/07/2017 - 05/13/2017	0.99	1.04
20	05/14/2017 - 05/20/2017	1.00	1.05
21	05/21/2017 - 05/27/2017	1.02	1.07
22	05/28/2017 - 06/03/2017	1.03	1.08
23	06/04/2017 - 06/10/2017	1.05	1.11
24	06/11/2017 - 06/17/2017	1.06	1.12
25	06/18/2017 - 06/24/2017	1.07	1.13
26	06/25/2017 - 07/01/2017	1.07	1.13
27	07/02/2017 - 07/08/2017	1.07	1.13
28	07/09/2017 - 07/15/2017	1.08	1.14
29	07/16/2017 - 07/22/2017	1.07	1.13
30	07/23/2017 - 07/29/2017	1.06	1.12
31	07/30/2017 - 08/05/2017	1.05	1.11
32	08/06/2017 - 08/12/2017	1.04	1.09
33	08/13/2017 - 08/19/2017	1.04	1.09
34	08/20/2017 - 08/26/2017	1.05	1.11
35	08/27/2017 - 09/02/2017	1.06	1.12
36	09/03/2017 - 09/09/2017	1.08	1.14
37	09/10/2017 - 09/16/2017	1.09	1.15
38	09/17/2017 - 09/23/2017	1.07	1.13
39	09/24/2017 - 09/30/2017	1.05	1.11
40	10/01/2017 - 10/07/2017	1.03	1.08
41	10/08/2017 - 10/14/2017	1.01	1.06
42	10/15/2017 - 10/21/2017	0.99	1.04
43	10/22/2017 - 10/28/2017	0.99	1.04
44	10/29/2017 - 11/04/2017	0.99	1.04
45	11/05/2017 - 11/11/2017	0.99	1.04
46	11/12/2017 - 11/18/2017	1.00	1.05
47	11/19/2017 - 11/25/2017	1.00	1.05
48	11/26/2017 - 12/02/2017	1.00	1.05
49	12/03/2017 - 12/09/2017	0.99	1.04
50	12/10/2017 - 12/16/2017	0.99	1.04
51	12/17/2017 - 12/23/2017	0.99	1.04
52	12/24/2017 - 12/30/2017	0.99	1.04
53	12/31/2017 - 12/31/2017	1.00	1.05

* PEAK SEASON

02-MAR-2018 15:35:06

830UPD

5_1100_PKSEASON.TXT

Appendix E

HCM Analysis Worksheets - Existing Conditions & Signal Timings

HCM 6th Signalized Intersection Summary

1: SR 19 & CR 48

02/11/2019

						
Movement	SEL	SET	NWT	NWR	SWL	SWR
Lane Configurations						
Traffic Volume (veh/h)	289	87	90	340	318	244
Future Volume (veh/h)	289	87	90	340	318	244
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00			1.00	1.00	1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No	No		No	
Adj Sat Flow, veh/h/ln	1737	1811	1767	1811	1752	1589
Adj Flow Rate, veh/h	332	100	103	0	366	280
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	11	6	9	6	10	21
Cap, veh/h	795	1152	682		379	306
Arrive On Green	0.19	0.64	0.39	0.00	0.23	0.23
Sat Flow, veh/h	1654	1811	1767	1535	1668	1346
Grp Volume(v), veh/h	332	100	103	0	366	280
Grp Sat Flow(s),veh/h/ln	1654	1811	1767	1535	1668	1346
Q Serve(g_s), s	10.3	2.1	3.8	0.0	21.7	20.3
Cycle Q Clear(g_c), s	10.3	2.1	3.8	0.0	21.7	20.3
Prop In Lane	1.00			1.00	1.00	1.00
Lane Grp Cap(c), veh/h	795	1152	682		379	306
V/C Ratio(X)	0.42	0.09	0.15		0.97	0.92
Avail Cap(c_a), veh/h	795	1152	682		379	306
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	0.00	1.00	1.00
Uniform Delay (d), s/veh	10.7	7.0	20.0	0.0	38.3	37.7
Incr Delay (d2), s/veh	1.6	0.1	0.5	0.0	38.5	33.9
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	3.6	0.7	1.6	0.0	12.5	9.2
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	12.3	7.2	20.5	0.0	76.8	71.6
LnGrp LOS	B	A	C		E	E
Approach Vol, veh/h		432	103	A	646	
Approach Delay, s/veh		11.1	20.5		74.6	
Approach LOS		B	C		E	
Timer - Assigned Phs	1	2		4		6
Phs Duration (G+Y+Rc), s	25.0	45.0		30.0		70.0
Change Period (Y+Rc), s	6.5	6.4		7.3		6.4
Max Green Setting (Gmax), s	18.5	38.6		22.7		38.6
Max Q Clear Time (g_c+I1), s	12.3	5.8		23.7		4.1
Green Ext Time (p_c), s	0.5	0.5		0.0		0.5
Intersection Summary						
HCM 6th Ctrl Delay			46.6			
HCM 6th LOS			D			

Notes

Unsignalized Delay for [NWR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th Signalized Intersection Summary

1: SR 19 & CR 48

02/11/2019

						
Movement	SEL	SET	NWT	NWR	SWL	SWR
Lane Configurations						
Traffic Volume (veh/h)	299	67	78	358	400	405
Future Volume (veh/h)	299	67	78	358	400	405
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00			1.00	1.00	1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No	No		No	
Adj Sat Flow, veh/h/ln	1856	1900	1811	1841	1841	1856
Adj Flow Rate, veh/h	322	72	84	0	430	435
Peak Hour Factor	0.93	0.93	0.93	0.93	0.93	0.93
Percent Heavy Veh, %	3	0	6	4	4	3
Cap, veh/h	863	1208	699		398	357
Arrive On Green	0.19	0.64	0.39	0.00	0.23	0.23
Sat Flow, veh/h	1767	1900	1811	1560	1753	1572
Grp Volume(v), veh/h	322	72	84	0	430	435
Grp Sat Flow(s),veh/h/ln	1767	1900	1811	1560	1753	1572
Q Serve(g_s), s	9.1	1.4	3.0	0.0	22.7	22.7
Cycle Q Clear(g_c), s	9.1	1.4	3.0	0.0	22.7	22.7
Prop In Lane	1.00			1.00	1.00	1.00
Lane Grp Cap(c), veh/h	863	1208	699		398	357
V/C Ratio(X)	0.37	0.06	0.12		1.08	1.22
Avail Cap(c_a), veh/h	863	1208	699		398	357
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	0.00	1.00	1.00
Uniform Delay (d), s/veh	10.4	6.9	19.8	0.0	38.7	38.7
Incr Delay (d2), s/veh	1.2	0.1	0.4	0.0	68.4	121.2
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	3.4	0.5	1.3	0.0	16.8	20.3
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	11.6	7.0	20.1	0.0	107.1	159.9
LnGrp LOS	B	A	C		F	F
Approach Vol, veh/h		394	84	A	865	
Approach Delay, s/veh		10.8	20.1		133.6	
Approach LOS		B	C		F	
Timer - Assigned Phs	1	2		4		6
Phs Duration (G+Y+Rc), s	25.0	45.0		30.0		70.0
Change Period (Y+Rc), s	6.5	6.4		7.3		6.4
Max Green Setting (Gmax), s	18.5	38.6		22.7		38.6
Max Q Clear Time (g_c+I1), s	11.1	5.0		24.7		3.4
Green Ext Time (p_c), s	0.6	0.4		0.0		0.3
Intersection Summary						
HCM 6th Ctrl Delay			90.5			
HCM 6th LOS			F			

Notes

Unsignalized Delay for [NWR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th TWSC
2: SR 19 & W Central Ave/E Central Ave

02/11/2019

Intersection												
Int Delay, s/veh	2											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	25	8	9	10	8	7	13	358	16	19	365	19
Future Vol, veh/h	25	8	9	10	8	7	13	358	16	19	365	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	86	86	86	86	86	86	86	86	86	86	86	86
Heavy Vehicles, %	12	33	2	2	2	2	38	10	2	42	2	11
Mvmt Flow	29	9	10	12	9	8	15	416	19	22	424	22
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	943	944	435	945	946	426	446	0	0	435	0	0
Stage 1	479	479	-	456	456	-	-	-	-	-	-	-
Stage 2	464	465	-	489	490	-	-	-	-	-	-	-
Critical Hdwy	7.22	6.83	6.22	7.12	6.52	6.22	4.48	-	-	4.52	-	-
Critical Hdwy Stg 1	6.22	5.83	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.22	5.83	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.608	4.297	3.318	3.518	4.018	3.318	2.542	-	-	2.578	-	-
Pot Cap-1 Maneuver	233	233	621	242	262	628	948	-	-	941	-	-
Stage 1	549	506	-	584	568	-	-	-	-	-	-	-
Stage 2	560	514	-	561	549	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	215	221	621	221	249	628	948	-	-	941	-	-
Mov Cap-2 Maneuver	215	221	-	221	249	-	-	-	-	-	-	-
Stage 1	537	490	-	572	556	-	-	-	-	-	-	-
Stage 2	532	503	-	524	532	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	22.7		19.2			0.3			0.4			
HCM LOS	C		C									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	948	-	-	252	282	941	-	-				
HCM Lane V/C Ratio	0.016	-	-	0.194	0.103	0.023	-	-				
HCM Control Delay (s)	8.9	0	-	22.7	19.2	8.9	0	-				
HCM Lane LOS	A	A	-	C	C	A	A	-				
HCM 95th %tile O(veh)	0	-	-	0.7	0.3	0.1	-	-				

HCM 6th TWSC
2: SR 19 & W Central Ave/E Central Ave

02/11/2019

Intersection												
Int Delay, s/veh	2.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	35	10	14	12	10	9	9	388	10	13	410	31
Future Vol, veh/h	35	10	14	12	10	9	9	388	10	13	410	31
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	91	91	91	91	91	91	91	91	91	91	91	91
Heavy Vehicles, %	9	2	29	2	2	2	44	5	2	2	5	8
Mvmt Flow	38	11	15	13	11	10	10	426	11	14	451	34
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	958	953	468	961	965	432	485	0	0	437	0	0
Stage 1	496	496	-	452	452	-	-	-	-	-	-	-
Stage 2	462	457	-	509	513	-	-	-	-	-	-	-
Critical Hdwy	7.19	6.52	6.49	7.12	6.52	6.22	4.54	-	-	4.12	-	-
Critical Hdwy Stg 1	6.19	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.19	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.581	4.018	3.561	3.518	4.018	3.318	2.596	-	-	2.218	-	-
Pot Cap-1 Maneuver	230	259	543	236	255	624	891	-	-	1123	-	-
Stage 1	543	545	-	587	570	-	-	-	-	-	-	-
Stage 2	567	568	-	547	536	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	213	251	543	216	247	624	891	-	-	1123	-	-
Mov Cap-2 Maneuver	213	251	-	216	247	-	-	-	-	-	-	-
Stage 1	535	536	-	578	561	-	-	-	-	-	-	-
Stage 2	539	559	-	512	527	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	23.7		19.6			0.2			0.2			
HCM LOS	C		C									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	891	-	-	257	281	1123	-	-				
HCM Lane V/C Ratio	0.011	-	-	0.252	0.121	0.013	-	-				
HCM Control Delay (s)	9.1	0	-	23.7	19.6	8.2	0	-				
HCM Lane LOS	A	A	-	C	C	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	1	0.4	0	-	-				

HCM 6th TWSC
3: SR 19 & S Florida Ave

02/11/2019

Intersection												
Int Delay, s/veh	14.9											
Movement	NBL	NBT	NBR	SBL	SBT	SBR	NEL	NET	NER	SWL	SWT	SWR
Lane Configurations		↰	↱		↰		↰	↱	↱	↰	↱	
Traffic Vol, veh/h	18	375	12	8	369	2	6	4	21	33	3	19
Future Vol, veh/h	18	375	12	8	369	2	6	4	21	33	3	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	0	-	-	-	250	-	250	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	93	93	93	93	93	93	93	93	93	93	93	93
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	19	403	13	9	397	2	6	4	23	35	3	20

Major/Minor	Minor1		Minor2		Major1			Major2				
Conflicting Flow All	299	109	4	319	122	13	23	0	0	27	0	0
Stage 1	16	16	-	83	83	-	-	-	-	-	-	-
Stage 2	283	93	-	236	39	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	653	781	1080	634	768	1067	1592	-	-	1587	-	-
Stage 1	1004	882	-	925	826	-	-	-	-	-	-	-
Stage 2	724	818	-	767	862	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	372	761	1080	358	748	1067	1592	-	-	1587	-	-
Mov Cap-2 Maneuver	372	761	-	358	748	-	-	-	-	-	-	-
Stage 1	1000	878	-	921	808	-	-	-	-	-	-	-
Stage 2	360	800	-	408	859	-	-	-	-	-	-	-

Approach	NB		SB		NE		SW	
HCM Control Delay, s	16.4		15.9		1.4		4.4	
HCM LOS	C		C					

Minor Lane/Major Mvmt	NEL	NET	NER	NBLn1	NBLn2	SBLn1	SWL	SWT	SWR
Capacity (veh/h)	1592	-	-	726	1080	732	1587	-	-
HCM Lane V/C Ratio	0.004	-	-	0.582	0.012	0.557	0.022	-	-
HCM Control Delay (s)	7.3	-	-	16.6	8.4	15.9	7.3	-	-
HCM Lane LOS	A	-	-	C	A	C	A	-	-
HCM 95th %tile Q(veh)	0	-	-	3.8	0	3.5	0.1	-	-

HCM 6th TWSC
3: SR 19 & S Florida Ave

02/11/2019

Intersection												
Int Delay, s/veh	15.9											
Movement	NBL	NBT	NBR	SBL	SBT	SBR	NEL	NET	NER	SWL	SWT	SWR
Lane Configurations		↱	↱		↱		↱	↱	↱	↱	↱	
Traffic Vol, veh/h	10	391	14	17	418	2	3	4	11	13	2	13
Future Vol, veh/h	10	391	14	17	418	2	3	4	11	13	2	13
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	0	-	-	-	250	-	250	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	89	89	89	89	89	89	89	89	89	89	89	89
Heavy Vehicles, %	2	4	2	2	19	2	33	2	9	2	2	8
Mvmt Flow	11	439	16	19	470	2	3	4	12	15	2	15
Major/Minor	Minor1		Minor2		Major1			Major2				
Conflicting Flow All	286	57	4	284	62	10	17	0	0	16	0	0
Stage 1	10	10	-	40	40	-	-	-	-	-	-	-
Stage 2	276	47	-	244	22	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.54	6.22	7.12	6.69	6.22	4.43	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.54	-	6.12	5.69	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.54	-	6.12	5.69	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.036	3.318	3.518	4.171	3.318	2.497	-	-	2.218	-	-
Pot Cap-1 Maneuver	666	830	1080	668	797	1071	1420	-	-	1602	-	-
Stage 1	1011	883	-	975	829	-	-	-	-	-	-	-
Stage 2	730	852	-	760	844	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	346	821	1080	377	788	1071	1420	-	-	1602	-	-
Mov Cap-2 Maneuver	346	821	-	377	788	-	-	-	-	-	-	-
Stage 1	1009	881	-	973	822	-	-	-	-	-	-	-
Stage 2	309	844	-	375	842	-	-	-	-	-	-	-
Approach	NB		SB		NE			SW				
HCM Control Delay, s	15.1		18.1		1.3			3.4				
HCM LOS	C		C									
Minor Lane/Major Mvmt	NEL	NET	NER	NBLn1	NBLn2	SBLn1	SWL	SWT	SWR			
Capacity (veh/h)	1420	-	-	794	1080	757	1602	-	-			
HCM Lane V/C Ratio	0.002	-	-	0.567	0.015	0.649	0.009	-	-			
HCM Control Delay (s)	7.5	-	-	15.3	8.4	18.1	7.3	-	-			
HCM Lane LOS	A	-	-	C	A	C	A	-	-			
HCM 95th %tile Q(veh)	0	-	-	3.6	0	4.8	0	-	-			

Intersection

Int Delay, s/veh 0.2

Movement	EBL	EBR	NBL	NBT	NBR	SBL	SBT	SBR	SWU	SWL	SWR
Lane Configurations											
Traffic Vol, veh/h	0	0	0	405	42	1	346	0	9	0	6
Future Vol, veh/h	0	0	0	405	42	1	346	0	9	0	6
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop
RT Channelized	-	None	-	-	None	-	-	None	-	-	-
Storage Length	0	-	-	-	-	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	-	-	0	-	-	0	-
Grade, %	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	84	84	84	84	84	84	84	84	84	84	84
Heavy Vehicles, %	2	2	2	8	12	2	10	2	2	2	2
Mvmt Flow	0	0	0	482	50	1	412	0	11	0	7

Major/Minor	Minor2		Major1		Major2		Minor1				
Conflicting Flow All	925	412	-	0	0	532	0	0	0	921	507
Stage 1	414	-	-	-	-	-	-	-	0	507	-
Stage 2	511	-	-	-	-	-	-	-	0	414	-
Critical Hdwy	7.12	6.22	-	-	-	4.12	-	-	-	7.12	6.22
Critical Hdwy Stg 1	6.12	-	-	-	-	-	-	-	-	6.12	-
Critical Hdwy Stg 2	6.12	-	-	-	-	-	-	-	-	6.12	-
Follow-up Hdwy	3.518	3.318	-	-	-	2.218	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	250	640	0	-	-	1036	-	0	0	251	566
Stage 1	616	-	0	-	-	-	-	0	0	548	-
Stage 2	545	-	0	-	-	-	-	0	0	616	-
Platoon blocked, %				-	-		-		-		
Mov Cap-1 Maneuver	247	640	-	-	-	1036	-	-	0	251	566
Mov Cap-2 Maneuver	247	-	-	-	-	-	-	-	0	251	-
Stage 1	616	-	-	-	-	-	-	-	0	548	-
Stage 2	538	-	-	-	-	-	-	-	0	615	-

Approach	EB	NB	SB	SW
HCM Control Delay, s	0	0	0	11.4
HCM LOS	A			B

Minor Lane/Major Mvmt	NBT	NBR	EBLn1	SBL	SBTSWLn1
Capacity (veh/h)	-	-	-	1036	- 566
HCM Lane V/C Ratio	-	-	-	0.001	- 0.013
HCM Control Delay (s)	-	-	0	8.5	0 11.4
HCM Lane LOS	-	-	A	A	A B
HCM 95th %tile Q(veh)	-	-	-	0	- 0

Intersection											
Int Delay, s/veh	0.2										
Movement	EBL	EBR	NBL	NBT	NBR	SBL	SBT	SBR	SWU	SWL	SWR
Lane Configurations											
Traffic Vol, veh/h	1	1	0	373	12	5	423	0	7	0	3
Future Vol, veh/h	1	1	0	373	12	5	423	0	7	0	3
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop
RT Channelized	-	None	-	-	None	-	-	None	-	-	-
Storage Length	0	-	-	-	-	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	-	-	0	-	-	0	-
Grade, %	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	3	2	2	10	2	2	2	2
Mvmt Flow	1	1	0	414	13	6	470	0	8	0	3
Major/Minor	Minor2		Major1		Major2			Minor1			
Conflicting Flow All	904	470	-	0	0	427	0	0	0	904	421
Stage 1	482	-	-	-	-	-	-	-	0	421	-
Stage 2	422	-	-	-	-	-	-	-	0	483	-
Critical Hdwy	7.12	6.22	-	-	-	4.12	-	-	-	7.12	6.22
Critical Hdwy Stg 1	6.12	-	-	-	-	-	-	-	-	6.12	-
Critical Hdwy Stg 2	6.12	-	-	-	-	-	-	-	-	6.12	-
Follow-up Hdwy	3.518	3.318	-	-	-	2.218	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	258	594	0	-	-	1132	-	0	0	258	632
Stage 1	565	-	0	-	-	-	-	0	0	610	-
Stage 2	609	-	0	-	-	-	-	0	0	565	-
Platoon blocked, %				-	-		-				
Mov Cap-1 Maneuver	255	594	-	-	-	1132	-	-	0	255	632
Mov Cap-2 Maneuver	255	-	-	-	-	-	-	-	0	255	-
Stage 1	565	-	-	-	-	-	-	-	0	610	-
Stage 2	606	-	-	-	-	-	-	-	0	559	-
Approach	EB		NB		SB			SW			
HCM Control Delay, s	14.7		0		0.1			10.7			
HCM LOS	B							B			
Minor Lane/Major Mvmt	NBT		NBR		EBLn1	SBL	SBT	SWLn1			
Capacity (veh/h)	-		-		374	1132	-	632			
HCM Lane V/C Ratio	-		-		0.006	0.005	-	0.005			
HCM Control Delay (s)	-		-		14.7	8.2	0	10.7			
HCM Lane LOS	-		-		B	A	A	B			
HCM 95th %tile Q(veh)	-		-		0	0	-	0			

HCM 6th TWSC
5: Orange Blossom Rd & SR 19

02/11/2019

Intersection						
Int Delay, s/veh	0.3					
Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	6	9	1	438	350	3
Future Vol, veh/h	6	9	1	438	350	3
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	8	10	2
Mvmt Flow	7	11	1	515	412	4

Major/Minor	Minor2	Major1	Major2			
Conflicting Flow All	931	414	416	0	-	0
Stage 1	414	-	-	-	-	-
Stage 2	517	-	-	-	-	-
Critical Hdwy	6.42	6.22	4.12	-	-	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	2.218	-	-	-
Pot Cap-1 Maneuver	296	638	1143	-	-	-
Stage 1	667	-	-	-	-	-
Stage 2	598	-	-	-	-	-
Platoon blocked, %				-	-	-
Mov Cap-1 Maneuver	296	638	1143	-	-	-
Mov Cap-2 Maneuver	296	-	-	-	-	-
Stage 1	666	-	-	-	-	-
Stage 2	598	-	-	-	-	-

Approach	EB	NB	SB
HCM Control Delay, s	13.6	0	0
HCM LOS	B		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	1143	-	436	-	-
HCM Lane V/C Ratio	0.001	-	0.04	-	-
HCM Control Delay (s)	8.2	0	13.6	-	-
HCM Lane LOS	A	A	B	-	-
HCM 95th %tile Q(veh)	0	-	0.1	-	-

HCM 6th TWSC
5: Orange Blossom Rd & SR 19

02/11/2019

Intersection

Int Delay, s/veh 0.2

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	6	2	5	385	423	8
Future Vol, veh/h	6	2	5	385	423	8
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	6	2	2	3	6	2
Mvmt Flow	7	2	6	453	498	9

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	968	503	507
Stage 1	503	-	-
Stage 2	465	-	-
Critical Hdwy	6.46	6.22	4.12
Critical Hdwy Stg 1	5.46	-	-
Critical Hdwy Stg 2	5.46	-	-
Follow-up Hdwy	3.554	3.318	2.218
Pot Cap-1 Maneuver	277	569	1058
Stage 1	599	-	-
Stage 2	624	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	275	569	1058
Mov Cap-2 Maneuver	275	-	-
Stage 1	594	-	-
Stage 2	624	-	-

Approach	EB	NB	SB
HCM Control Delay, s	16.7	0.1	0
HCM LOS	C		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	1058	-	316	-	-
HCM Lane V/C Ratio	0.006	-	0.03	-	-
HCM Control Delay (s)	8.4	0	16.7	-	-
HCM Lane LOS	A	A	C	-	-
HCM 95th %tile Q(veh)	0	-	0.1	-	-

Intersection

Int Delay, s/veh 3.2

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	78	62	359	74	64	364
Future Vol, veh/h	78	62	359	74	64	364
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	-	590	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	38	15	8	22	9	5
Mvmt Flow	80	64	370	76	66	375

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	877	370	0
Stage 1	370	-	-
Stage 2	507	-	-
Critical Hdwy	6.78	6.35	-
Critical Hdwy Stg 1	5.78	-	-
Critical Hdwy Stg 2	5.78	-	-
Follow-up Hdwy	3.842	3.435	-
Pot Cap-1 Maneuver	277	648	-
Stage 1	626	-	-
Stage 2	538	-	-
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	256	648	-
Mov Cap-2 Maneuver	256	-	-
Stage 1	626	-	-
Stage 2	497	-	-

Approach	WB	NB	SB
HCM Control Delay, s	19.1	0	1.3
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1WBLn2	SBL	SBT
Capacity (veh/h)	-	-	256	648
HCM Lane V/C Ratio	-	-	0.314	0.099
HCM Control Delay (s)	-	-	25.4	11.2
HCM Lane LOS	-	-	D	B
HCM 95th %tile Q(veh)	-	-	1.3	0.3

Intersection

Int Delay, s/veh 2.9

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	82	57	446	80	49	459
Future Vol, veh/h	82	57	446	80	49	459
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	-	590	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	5	2	2	15	6	2
Mvmt Flow	85	59	460	82	51	473

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	1035	460	0
Stage 1	460	-	-
Stage 2	575	-	-
Critical Hdwy	6.45	6.22	-
Critical Hdwy Stg 1	5.45	-	-
Critical Hdwy Stg 2	5.45	-	-
Follow-up Hdwy	3.545	3.318	-
Pot Cap-1 Maneuver	254	601	-
Stage 1	629	-	-
Stage 2	557	-	-
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	236	601	-
Mov Cap-2 Maneuver	236	-	-
Stage 1	629	-	-
Stage 2	519	-	-

Approach	WB	NB	SB
HCM Control Delay, s	21.6	0	0.8
HCM LOS	C		

Minor Lane/Major Mvmt	NBT	NBRWBLn1WBLn2	SBL	SBT
Capacity (veh/h)	-	- 236 601 1007	-	-
HCM Lane V/C Ratio	-	- 0.358 0.098	0.05	-
HCM Control Delay (s)	-	- 28.5 11.6	8.8	0
HCM Lane LOS	-	- D B	A	A
HCM 95th %tile Q(veh)	-	- 1.5 0.3	0.2	-

HCM 6th Signalized Intersection Summary

7: SR 19 Off Ramp/Turn Pike Off Ramp & US 27

02/11/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	224	795	30	43	854	127	45	156	96	91	75	134
Future Volume (veh/h)	224	795	30	43	854	127	45	156	96	91	75	134
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1796	1841	1648	1826	1841	1722	1870	1870	1870	1841	1870	1841
Adj Flow Rate, veh/h	241	855	0	46	918	0	48	168	103	98	81	0
Peak Hour Factor	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
Percent Heavy Veh, %	7	4	17	5	4	12	2	2	2	4	2	4
Cap, veh/h	271	1062		275	1062		70	192	111	232	715	
Arrive On Green	0.16	0.30	0.00	0.16	0.30	0.00	0.20	0.20	0.20	0.13	0.38	0.00
Sat Flow, veh/h	1711	3497	1397	1739	3497	1459	198	945	545	1753	1870	1560
Grp Volume(v), veh/h	241	855	0	46	918	0	319	0	0	98	81	0
Grp Sat Flow(s),veh/h/ln	1711	1749	1397	1739	1749	1459	1689	0	0	1753	1870	1560
Q Serve(g_s), s	19.3	31.5	0.0	3.2	34.7	0.0	19.9	0.0	0.0	7.2	3.9	0.0
Cycle Q Clear(g_c), s	19.3	31.5	0.0	3.2	34.7	0.0	25.9	0.0	0.0	7.2	3.9	0.0
Prop In Lane	1.00		1.00	1.00		1.00	0.15		0.32	1.00		1.00
Lane Grp Cap(c), veh/h	271	1062		275	1062		373	0	0	232	715	
V/C Ratio(X)	0.89	0.81		0.17	0.86		0.85	0.00	0.00	0.42	0.11	
Avail Cap(c_a), veh/h	271	1062		275	1062		373	0	0	232	715	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	57.7	44.9	0.0	51.0	46.0	0.0	54.6	0.0	0.0	55.8	27.9	0.0
Incr Delay (d2), s/veh	32.2	6.5	0.0	1.3	9.4	0.0	21.3	0.0	0.0	5.6	0.3	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	10.5	14.0	0.0	1.5	15.7	0.0	13.2	0.0	0.0	3.5	1.8	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	89.9	51.5	0.0	52.3	55.4	0.0	75.9	0.0	0.0	61.4	28.3	0.0
LnGrp LOS	F	D		D	E		E	A	A	E	C	
Approach Vol, veh/h		1096	A		964	A		319			179	A
Approach Delay, s/veh		59.9			55.3			75.9			46.4	
Approach LOS		E			E			E			D	
Timer - Assigned Phs	1	2		4	5	6	7	8				
Phs Duration (G+Y+Rc), s	30.0	50.0		60.0	30.0	50.0	25.0	35.0				
Change Period (Y+Rc), s	* 7.8	7.5		6.5	7.9	7.5	6.5	6.5				
Max Green Setting (Gmax), s	* 22	42.5		28.5	22.1	42.5	18.5	28.5				
Max Q Clear Time (g_c+I1), s	21.3	36.7		5.9	5.2	33.5	9.2	27.9				
Green Ext Time (p_c), s	0.1	2.7		0.3	0.1	3.4	0.1	0.1				

Intersection Summary

HCM 6th Ctrl Delay	59.2
HCM 6th LOS	E

Notes

* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.

Unsignalized Delay for [EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th Signalized Intersection Summary

7: SR 19 Off Ramp/Turn Pike Off Ramp & US 27

02/11/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	306	783	53	127	775	91	69	55	111	154	187	219
Future Volume (veh/h)	306	783	53	127	775	91	69	55	111	154	187	219
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1767	1841	1781	1870	1826	1826	1841	1841	1841	1870	1870	1811
Adj Flow Rate, veh/h	306	783	0	127	775	0	69	55	111	154	187	0
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Percent Heavy Veh, %	9	4	8	2	5	5	4	4	4	2	2	6
Cap, veh/h	267	1062		281	1053		110	85	144	235	715	
Arrive On Green	0.16	0.30	0.00	0.16	0.30	0.00	0.20	0.20	0.20	0.13	0.38	0.00
Sat Flow, veh/h	1682	3497	1510	1781	3469	1547	375	417	709	1781	1870	1535
Grp Volume(v), veh/h	306	783	0	127	775	0	235	0	0	154	187	0
Grp Sat Flow(s),veh/h/ln	1682	1749	1510	1781	1735	1547	1502	0	0	1781	1870	1535
Q Serve(g_s), s	22.2	28.1	0.0	9.1	28.0	0.0	16.7	0.0	0.0	11.5	9.6	0.0
Cycle Q Clear(g_c), s	22.2	28.1	0.0	9.1	28.0	0.0	20.5	0.0	0.0	11.5	9.6	0.0
Prop In Lane	1.00		1.00	1.00		1.00	0.29		0.47	1.00		1.00
Lane Grp Cap(c), veh/h	267	1062		281	1053		339	0	0	235	715	
V/C Ratio(X)	1.15	0.74		0.45	0.74		0.69	0.00	0.00	0.65	0.26	
Avail Cap(c_a), veh/h	267	1062		281	1053		339	0	0	235	715	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	58.9	43.7	0.0	53.5	43.7	0.0	52.3	0.0	0.0	57.7	29.7	0.0
Incr Delay (d2), s/veh	100.7	4.6	0.0	5.2	4.6	0.0	11.1	0.0	0.0	13.3	0.9	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	16.6	12.3	0.0	4.3	12.2	0.0	8.8	0.0	0.0	6.0	4.5	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	159.6	48.3	0.0	58.6	48.3	0.0	63.5	0.0	0.0	71.0	30.6	0.0
LnGrp LOS	F	D		E	D		E	A	A	E	C	
Approach Vol, veh/h	1089		A	902		A	235			341		A
Approach Delay, s/veh	79.6			49.8			63.5			48.9		
Approach LOS	E			D			E			D		
Timer - Assigned Phs	1	2		4	5	6	7	8				
Phs Duration (G+Y+Rc), s	30.0	50.0		60.0	30.0	50.0	25.0	35.0				
Change Period (Y+Rc), s	* 7.8	7.5		6.5	7.9	7.5	6.5	6.5				
Max Green Setting (Gmax), s	* 22	42.5		28.5	22.1	42.5	18.5	28.5				
Max Q Clear Time (g_c+I1), s	24.2	30.0		11.6	11.1	30.1	13.5	22.5				
Green Ext Time (p_c), s	0.0	3.7		0.8	0.2	3.7	0.2	0.6				

Intersection Summary

HCM 6th Ctrl Delay	63.5
HCM 6th LOS	E

Notes

* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.

Unsignalized Delay for [EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th TWSC
8: US 27 & SR 19 Off Ramp

02/11/2019

Intersection												
Int Delay, s/veh	1.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	124	918	0	4	869	117	0	0	0	54	0	172
Future Vol, veh/h	124	918	0	4	869	117	0	0	0	54	0	172
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	Free	-	-	None	-	-	Free
Storage Length	320	-	-	-	-	480	-	-	-	0	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	16974	-	-	1	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	97	97	97	97	97	97	97	97	97	97	97	97
Heavy Vehicles, %	3	3	2	2	4	5	0	0	0	2	0	6
Mvmt Flow	128	946	0	4	896	121	0	0	0	56	0	177
Major/Minor	Major1			Major2			Minor2					
Conflicting Flow All	896	0	-	946	0	0				1633	-	-
Stage 1	-	-	-	-	-	-				904	-	-
Stage 2	-	-	-	-	-	-				729	-	-
Critical Hdwy	4.16	-	-	4.14	-	-				6.84	-	-
Critical Hdwy Stg 1	-	-	-	-	-	-				5.84	-	-
Critical Hdwy Stg 2	-	-	-	-	-	-				5.84	-	-
Follow-up Hdwy	2.23	-	-	2.22	-	-				3.52	-	-
Pot Cap-1 Maneuver	747	-	0	721	-	0				92	0	0
Stage 1	-	-	0	-	-	0				355	0	0
Stage 2	-	-	0	-	-	0				438	0	0
Platoon blocked, %		-			-							
Mov Cap-1 Maneuver	747	-	-	721	-	-				75	0	-
Mov Cap-2 Maneuver	-	-	-	-	-	-				192	0	-
Stage 1	-	-	-	-	-	-				294	0	-
Stage 2	-	-	-	-	-	-				433	0	-
Approach	EB			WB			SB					
HCM Control Delay, s	1.3			0.1						31.2		
HCM LOS										D		
Minor Lane/Major Mvmt	EBL	EBT	WBL	WBT	SBLn1	SBLn2						
Capacity (veh/h)	747	-	721	-	192	-						
HCM Lane V/C Ratio	0.171	-	0.006	-	0.29	-						
HCM Control Delay (s)	10.8	-	10	0.1	31.2	0						
HCM Lane LOS	B	-	B	A	D	A						
HCM 95th %tile Q(veh)	0.6	-	0	-	1.1	-						

HCM 6th TWSC
8: US 27 & SR 19 Off Ramp

02/11/2019

Intersection												
Int Delay, s/veh	1.6											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	↰	↑↑			↰	↰				↰		↰
Traffic Vol, veh/h	125	945	0	2	866	166	0	0	0	56	0	101
Future Vol, veh/h	125	945	0	2	866	166	0	0	0	56	0	101
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Free	Free	Stop	Stop	Stop	Stop	Stop	Stop
RT Channelized	-	-	None	-	-	Free	-	-	None	-	-	Free
Storage Length	320	-	-	-	-	480	-	-	-	0	-	0
Veh in Median Storage, #	-	0	-	-	0	-	-	16974	-	-	1	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	96	96	96	96	96	96	96	96	96	96	96	96
Heavy Vehicles, %	10	3	2	2	5	3	0	0	0	4	0	7
Mvmt Flow	130	984	0	2	902	173	0	0	0	58	0	105
Major/Minor	Major1			Major2			Minor2					
Conflicting Flow All	902	0	-	984	0	0	1658					
Stage 1	-	-	-	-	-	-	906					
Stage 2	-	-	-	-	-	-	752					
Critical Hdwy	4.3	-	-	4.14	-	-	6.88					
Critical Hdwy Stg 1	-	-	-	-	-	-	5.88					
Critical Hdwy Stg 2	-	-	-	-	-	-	5.88					
Follow-up Hdwy	2.3	-	-	2.22	-	-	3.54					
Pot Cap-1 Maneuver	701	-	0	698	-	0	87					
Stage 1	-	-	0	-	-	0	350					
Stage 2	-	-	0	-	-	0	421					
Platoon blocked, %	-			-								
Mov Cap-1 Maneuver	701	-	-	698	-	-	70					
Mov Cap-2 Maneuver	-	-	-	-	-	-	185					
Stage 1	-	-	-	-	-	-	285					
Stage 2	-	-	-	-	-	-	418					
Approach	EB			WB			SB					
HCM Control Delay, s	1.3			0			33.2					
HCM LOS							D					
Minor Lane/Major Mvmt	EBL	EBT	WBL	WBT	SBLn1	SBLn2						
Capacity (veh/h)	701	-	698	-	185	-						
HCM Lane V/C Ratio	0.186	-	0.003	-	0.315	-						
HCM Control Delay (s)	11.3	-	10.2	0	33.2	0						
HCM Lane LOS	B	-	B	A	D	A						
HCM 95th %tile Q(veh)	0.7	-	0	-	1.3	-						

LAKE COUNTY - TRAFFIC SIGNAL OPERATIONS

CARTEGRAPH ID: LC-S-043**DATE: 05/15/2015****INTERSECTION NAME AND ID#: SR 19 & CR 48 076**

PHASE	1	2	3	4	5	6	7	8
	EBL	WB		SB		EB		
INITIAL	8	15		8		15		
PASSAGE	3	3		3		3		
YELLOW	4.4	4.4		4.8		4.4		
RED CLEAR	2.1	2.0		2.5		2.0		
MAX 1	25	45		30		45		
MAX 2								
WALK								
DON'T WALK								
RECALL				SOFT				
DET. FUNC.	L	L		L		L		

SYSTEM TIMING

	CYCLE	OFFSET	COORDINATED		BASE DAY 1		BASE DAY 2	
PATTERN	Sec.	Sec.	Phase	Sequence	Mon.- Fri.		Sat.- Sun.	

SPLIT ALLOCATION - Sec.

PHASE	1	2	3	4	5	6	7	8

NOTES: Naztec 980

LAKE COUNTY - TRAFFIC SIGNAL OPERATIONS

CARTEGRAPH ID: LC-S-065**DATE: 05/15/2015****INTERSECTION NAME AND ID#: US 27 & SR 19 (TurnPike South) 046**

PHASE	1	2	3	4	5	6	7	8
	NBL	SB		WB	SBL	NB	WBL	EB
INITIAL	5	15		8	5	15	6	8
PASSAGE	3	3		3	3	3	3	3
YELLOW	5.5	5.5		3.4	5.5	5.5	3.4	3.4
RED CLEAR	2.3	2.0		3.1	2.4	2.0	3.1	3.1
MAX 1	30	50		35	30	50	25	35
MAX 2								
WALK								
DON'T WALK								
RECALL		Min				Min		
DET. FUNC.		L				L		

SPLIT ALLOCATION - Sec.

	CYCLE	OFFSET	COORDINATED		BASE DAY 1		BASE DAY 2	
PATTERN	Sec.	Sec.	Phase	Sequence	Mon.- Fri.		Sat.- Sun.	

SPLIT ALLOCATION - Sec.

PHASE	1	2	3	4	5	6	7	8

NOTES: Naztec TS-2

Appendix F
ITE Trip Generation Sheets

Single-Family Detached Housing (210)


Vehicle Trip Ends vs: Dwelling Units
On a: Weekday

Setting/Location: General Urban/Suburban
Number of Studies: 159
Avg. Num. of Dwelling Units: 264
Directional Distribution: 50% entering, 50% exiting

Vehicle Trip Generation per Dwelling Unit

Average Rate	Range of Rates	Standard Deviation
9.44	4.81 - 19.39	2.10

Data Plot and Equation



Single-Family Detached Housing (210)

Vehicle Trip Ends vs: Dwelling Units

On a: Weekday,

Peak Hour of Adjacent Street Traffic,
One Hour Between 7 and 9 a.m.

Setting/Location: General Urban/Suburban

Number of Studies: 173


Avg. Num. of Dwelling Units: 219

Directional Distribution: 25% entering, 75% exiting

Vehicle Trip Generation per Dwelling Unit

Average Rate	Range of Rates	Standard Deviation
0.74	0.33 - 2.27	0.27

Data Plot and Equation




Single-Family Detached Housing (210)

Vehicle Trip Ends vs: Dwelling Units
 On a: Weekday,
 Peak Hour of Adjacent Street Traffic,
 One Hour Between 4 and 6 p.m.
 Setting/Location: General Urban/Suburban
 Number of Studies: 190
 Avg. Num. of Dwelling Units: 242
 Directional Distribution: 63% entering, 37% exiting


Vehicle Trip Generation per Dwelling Unit

Average Rate	Range of Rates	Standard Deviation
0.99	0.44 - 2.98	0.31

Data Plot and Equation



Appendix G
CFRPM Model Output



Pacific Ace (P19009 CF 2025 TAZ=1662)

Project Distribution

C:\FSUTMS\D5\CFRPMV61_Daily\Base\CF_2025\P19011\Output\HWYLOAD_C25.NET 1/28/2019

Appendix H
Growth Trend Analysis & Historical Traffic Counts

FLORIDA DEPARTMENT OF TRANSPORTATION
TRANSPORTATION STATISTICS OFFICE
2017 HISTORICAL AADT REPORT

COUNTY: 11 - LAKE

SITE: 0494 - ON SR-19, 0.3 MI. N OF CR-48 (RCLP) CAB NW


YEAR	AADT	DIRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
2017	14500 C	N 7400	S 7100	9.00	54.20	11.50
2016	13900 C	N 7000	S 6900	9.00	53.90	11.20
2015	12900 C	N 6400	S 6500	9.00	54.60	11.00
2014	12200 C	N 6100	S 6100	9.00	54.50	15.10
2013	12900 C	N 6500	S 6400	9.00	54.70	24.50
2012	11800 C	N 5900	S 5900	9.00	55.10	11.10
2011	10400 C	N 4600	S 5800	9.00	54.20	10.10
2010	11000 C	N 4900	S 6100	9.86	54.75	7.60
2009	12400 C	N 6200	S 6200	9.96	54.94	12.60
2008	12300 C	N 6300	S 6000	10.42	55.39	12.60
2007	14000 C	N 7000	S 7000	10.24	59.56	11.20
2006	14400 C	N 7200	S 7200	10.23	59.48	11.00
2005	13800 C	N 6800	S 7000	10.30	57.70	15.00
2004	13000 C	N 6500	S 6500	10.10	57.60	15.00
2003	12500 C	N 6200	S 6300	9.80	55.30	12.90
2002	12100 C	N 6200	S 5900	10.10	57.30	11.70

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE
S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; R = FOURTH YEAR ESTIMATE
V = FIFTH YEAR ESTIMATE; 6 = SIXTH YEAR ESTIMATE; X = UNKNOWN
*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

TRAFFIC TRENDS

SR 19 -- CR 561 to Lake Harris North End

County:	LAKE
Station #:	494
Highway:	SR 19



** Annual Trend Increase:	491
Trend R-squared:	82.0%
Trend Annual Historic Growth Rate:	4.24%
Trend Growth Rate (2017 to Design Year):	3.44%
Printed:	6-Feb-19

Straight Line Growth Option

Year	Traffic (ADT/AADT)	
	Count*	Trend**
2012	11800	11800
2013	12900	12300
2014	12200	12800
2015	12900	13300
2016	13900	13800
2017	14500	14300
2024 Opening Year Trend		
2024	N/A	17700
2030 Mid-Year Trend		
2030	N/A	20700
2040 Design Year Trend		
2040	N/A	25600
TRANPLAN Forecasts/Trends		

*Axle-Adjusted

FLORIDA DEPARTMENT OF TRANSPORTATION
TRANSPORTATION STATISTICS OFFICE
2017 HISTORICAL AADT REPORT

COUNTY: 11 - LAKE

SITE: 0495 - ON SR-19, 0.326 MI. S OF CR-48 (RVL)


YEAR	AADT	DIRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
----	-----	-----	-----	-----	-----	-----
2017	9200 C	N 4600	S 4600	9.00	54.20	16.50
2016	9100 C	N 4600	S 4500	9.00	53.90	19.70
2015	8700 C	N 4400	S 4300	9.00	54.60	13.90
2014	8200 C	N 4100	S 4100	9.00	54.50	15.80
2013	8700 C	N 4400	S 4300	9.00	54.70	16.70
2012	8200 C	N 4100	S 4100	9.00	55.10	14.80
2011	7900 C	N 4000	S 3900	9.00	54.20	15.10
2010	8200 C	N 4000	S 4200	9.86	54.75	13.50
2009	9000 C	N 4700	S 4300	9.96	54.94	9.90
2008	8200 C	N 4100	S 4100	10.42	55.39	16.40
2007	8800 C	N 4400	S 4400	10.24	59.56	18.60
2006	9200 C	N 4600	S 4600	10.23	59.48	21.50
2005	8800 C	N 4600	S 4200	10.30	57.70	14.50
2004	8100 C	N 4100	S 4000	10.10	57.60	21.90
2003	7600 C	N 3800	S 3800	9.80	55.30	19.80
2002	8800 C	N 4500	S 4300	10.10	57.30	14.90

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE
S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; R = FOURTH YEAR ESTIMATE
V = FIFTH YEAR ESTIMATE; 6 = SIXTH YEAR ESTIMATE; X = UNKNOWN
*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

TRAFFIC TRENDS

SR 19 -- CR 480 to Central Ave

County:	LAKE
Station #:	495
Highway:	SR 19



** Annual Trend Increase:	260
Trend R-squared:	83.6%
Trend Annual Historic Growth Rate:	3.29%
Trend Growth Rate (2017 to Design Year):	2.84%
Printed:	6-Feb-19

Straight Line Growth Option

Year	Traffic (ADT/AADT)	
	Count*	Trend**
2012	8200	7900
2013	7900	8200
2014	8200	8400
2015	8700	8700
2016	9100	8900
2017	9200	9200
2024 Opening Year Trend		
2024	N/A	11000
2030 Mid-Year Trend		
2030	N/A	12600
2040 Design Year Trend		
2040	N/A	15200
TRANPLAN Forecasts/Trends		

*Axle-Adjusted

FLORIDA DEPARTMENT OF TRANSPORTATION
TRANSPORTATION STATISTICS OFFICE
2017 HISTORICAL AADT REPORT

COUNTY: 11 - LAKE


SITE: 0255 - ON SR-19, 0.021 MI. S OF CR-455 (RVL) CAB NW

YEAR	AADT	DIRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
----	-----	-----	-----	-----	-----	-----
2017	11800 C	N 5800	S 6000	9.50	54.20	16.50
2016	9200 C	N 4600	S 4600	9.00	53.90	19.70
2015	8800 C	N 4400	S 4400	9.00	54.60	13.90
2014	8000 C	N 4000	S 4000	9.00	54.50	15.80
2013	8400 C	N 4100	S 4300	9.00	54.70	16.70
2012	8000 C	N 4000	S 4000	9.00	55.10	14.80
2011	7600 C	N 3800	S 3800	9.00	54.20	15.10
2010	7700 C	N 3900	S 3800	9.86	54.75	13.50
2009	7700 C	N 3900	S 3800	9.96	54.94	9.90
2008	8100 C	N 4100	S 4000	10.42	55.39	16.40
2007	8800 C	N 4400	S 4400	10.24	59.56	18.60
2006	9700 C	N 4800	S 4900	10.23	59.48	21.50
2005	8800 C	N 4400	S 4400	10.30	57.70	14.50
2004	8000 C	N 4000	S 4000	10.10	57.60	21.90
2003	7800 C	N 3900	S 3900	9.80	55.30	19.80
2002	9500 C	N 4800	S 4700	10.10	57.30	14.90

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE
S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; R = FOURTH YEAR ESTIMATE
V = FIFTH YEAR ESTIMATE; 6 = SIXTH YEAR ESTIMATE; X = UNKNOWN
*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

TRAFFIC TRENDS SR 19 -- Central Ave to CR 455

County:	LAKE
Station #:	255
Highway:	SR 19



** Annual Trend Increase:	634
Trend R-squared:	68.5%
Trend Annual Historic Growth Rate:	8.65%
Trend Growth Rate (2017 to Design Year):	5.99%
Printed:	6-Feb-19
Straight Line Growth Option	

Year	Traffic (ADT/AADT)	
	Count*	Trend**
2012	8000	7400
2013	8400	8100
2014	8000	8700
2015	8800	9400
2016	9200	10000
2017	11800	10600
2024 Opening Year Trend		
2024	N/A	15100
2030 Mid-Year Trend		
2030	N/A	18900
2040 Design Year Trend		
2040	N/A	25200
TRANPLAN Forecasts/Trends		

*Axle-Adjusted

FLORIDA DEPARTMENT OF TRANSPORTATION
TRANSPORTATION STATISTICS OFFICE
2017 HISTORICAL AADT REPORT

COUNTY: 97 - FL. TURNPIKE


SITE: 2851 - MAINLINE NB OFF RAMP TO US-27/LEESBURG SOUTH, M285A

YEAR	AADT	DIRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
----	-----	-----	-----	-----	-----	-----
2017	6150 C	N 6150	0	9.00	99.90	16.20
2016	5600 C	N 5600	0	9.00	99.90	16.60
2015	5050 C	N 5050	0	9.00	59.60	16.00
2014	4750 C	N 4750		9.00		15.20
2013	4500 C	N 4500	0	9.00		15.60
2012	4700 E	N 4700	0	9.00	99.90	14.80

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE
S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; R = FOURTH YEAR ESTIMATE
V = FIFTH YEAR ESTIMATE; 6 = SIXTH YEAR ESTIMATE; X = UNKNOWN
*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

TRAFFIC TRENDS
FL. Turnpike -- NB off Ramp to US 27

County:	LAKE
Station #:	97
Highway:	FL. Turnpike



** Annual Trend Increase:	420
Trend R-squared:	97.4%
Trend Annual Historic Growth Rate:	9.66%
Trend Growth Rate (2017 to Design Year):	6.84%
Printed:	8-Feb-19

Straight Line Growth Option

Year	Traffic (ADT/AADT)	
	Count*	Trend**
2013	4500	4400
2014	4800	4800
2015	5100	5200
2016	5600	5700
2017	6200	6100
2024 Opening Year Trend		
2024	N/A	9000
2030 Mid-Year Trend		
2030	N/A	11500
2040 Design Year Trend		
2040	N/A	15700
TRANPLAN Forecasts/Trends		

*Axle-Adjusted

FLORIDA DEPARTMENT OF TRANSPORTATION
TRANSPORTATION STATISTICS OFFICE
2017 HISTORICAL AADT REPORT

COUNTY: 11 - LAKE


SITE: 0363 - ON SR-25 (US-27), 0.133 MI SE OF SR 19 (RVL)

YEAR	AADT	DIRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
----	-----	-----	-----	-----	-----	-----
2017	19900 F	N 10000	S 9900	9.00	54.20	16.50
2016	19200 C	N 9700	S 9500	9.00	53.90	8.80
2015	20500 C	N 10000	S 10500	9.00	54.60	10.10
2014	20200 C	N 10500	S 9700	9.00	54.50	9.90
2013	15600 C	N 7000	S 8600	9.00	54.70	10.30
2012	16100 C	N 8300	S 7800	9.00	55.10	10.40
2011	16100 C	N 8100	S 8000	9.00	54.20	10.00
2010	16700 C	N 8500	S 8200	9.86	54.75	11.50
2009	16100 C	N 8200	S 7900	9.96	54.94	12.40
2008	17200 C	N 8800	S 8400	10.42	55.39	12.50
2007	19300 C	N 10000	S 9300	10.24	59.56	10.30
2006	20500 C	N 10500	S 10000	10.23	59.48	13.60
2005	23500 C	N 11500	S 12000	10.30	57.70	11.40
2004	18800 C	N 9500	S 9300	10.10	57.60	15.40
2003	16800 C	N 8500	S 8300	9.80	55.30	15.50
2002	16600 C	N 8600	S 8000	10.10	57.30	15.10

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE
S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; R = FOURTH YEAR ESTIMATE
V = FIFTH YEAR ESTIMATE; 6 = SIXTH YEAR ESTIMATE; X = UNKNOWN
*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

TRAFFIC TRENDS
US 27 -- 0.133 MI SE of S19

County:	LAKE
Station #:	363
Highway:	US 27



** Annual Trend Increase:	760
Trend R-squared:	35.9%
Trend Annual Historic Growth Rate:	4.26%
Trend Growth Rate (2017 to Design Year):	3.69%
Printed:	8-Feb-19
Straight Line Growth Option	

Year	Traffic (ADT/AADT)	
	Count*	Trend**
2013	15600	17600
2014	20200	18300
2015	20500	19100
2016	19200	19800
2017	19900	20600
2024 Opening Year Trend		
2024	N/A	25900
2030 Mid-Year Trend		
2030	N/A	30500
2040 Design Year Trend		
2040	N/A	38100
TRANPLAN Forecasts/Trends		

*Axle-Adjusted

FLORIDA DEPARTMENT OF TRANSPORTATION
TRANSPORTATION STATISTICS OFFICE
2017 HISTORICAL AADT REPORT

COUNTY: 11 - LAKE


SITE: 8090 - NUMBER TWO RD, 500 FT W OF PALM AVE - OFF SYSTEM

YEAR	AADT	DIRECTION 1	DIRECTION 2	*K FACTOR	D FACTOR	T FACTOR
----	-----	-----	-----	-----	-----	-----
2017	1250 C	E 650	W 600	9.00	54.20	10.70
2016	1600 R	E 800	W 800	9.00	53.90	12.60
2015	1500 T	E 750	W 750	9.00	54.60	12.60
2014	1500 S	E 750	W 750	9.00	54.50	11.30
2013	1500 F	E 750	W 750	9.50	54.70	10.90
2012	1500 C	E 750	W 750	9.50	55.10	11.00

AADT FLAGS: C = COMPUTED; E = MANUAL ESTIMATE; F = FIRST YEAR ESTIMATE
S = SECOND YEAR ESTIMATE; T = THIRD YEAR ESTIMATE; R = FOURTH YEAR ESTIMATE
V = FIFTH YEAR ESTIMATE; 6 = SIXTH YEAR ESTIMATE; X = UNKNOWN
*K FACTOR: STARTING WITH YEAR 2011 IS STANDARDK, PRIOR YEARS ARE K30 VALUES

TRAFFIC TRENDS Central ave -- West of SR 19

County:	LAKE
Station #:	255
Highway:	Central ave



Year	Traffic (ADT/AADT)	
	Count*	Trend**
2012	1500	1500
2013	1500	1500
2014	1500	1500
2015	1500	1500
2016	1600	1600
2017	1600	1600
2024 Opening Year Trend		
2024	N/A	1800
2030 Mid-Year Trend		
2030	N/A	1900
2040 Design Year Trend		
2040	N/A	2100
TRANPLAN Forecasts/Trends		

** Annual Trend Increase:	23
Trend R-squared:	68.6%
Trend Annual Historic Growth Rate:	1.33%
Trend Growth Rate (2017 to Design Year):	1.36%
Printed:	6-Feb-19
Straight Line Growth Option	

*Axle-Adjusted

Appendix I

HCM Worksheets – Projected Conditions & Intersection volume Projection

HCM 6th Signalized Intersection Summary

1: SR 19 & CR 48

02/19/2019



Movement	SEL	SET	NWT	NWR	SWL	SWR
Lane Configurations						
Traffic Volume (veh/h)	335	124	172	479	413	295
Future Volume (veh/h)	335	124	172	479	413	295
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00			1.00	1.00	1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No	No		No	
Adj Sat Flow, veh/h/ln	1737	1811	1767	1811	1752	1589
Adj Flow Rate, veh/h	385	143	198	0	475	339
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	11	6	9	6	10	21
Cap, veh/h	717	1152	682		379	306
Arrive On Green	0.19	0.64	0.39	0.00	0.23	0.23
Sat Flow, veh/h	1654	1811	1767	1535	1668	1346
Grp Volume(v), veh/h	385	143	198	0	475	339
Grp Sat Flow(s),veh/h/ln	1654	1811	1767	1535	1668	1346
Q Serve(g_s), s	12.4	3.1	7.8	0.0	22.7	22.7
Cycle Q Clear(g_c), s	12.4	3.1	7.8	0.0	22.7	22.7
Prop In Lane	1.00			1.00	1.00	1.00
Lane Grp Cap(c), veh/h	717	1152	682		379	306
V/C Ratio(X)	0.54	0.12	0.29		1.25	1.11
Avail Cap(c_a), veh/h	717	1152	682		379	306
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	0.00	1.00	1.00
Uniform Delay (d), s/veh	11.6	7.2	21.2	0.0	38.7	38.7
Incr Delay (d2), s/veh	2.9	0.2	1.1	0.0	134.4	84.1
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	4.5	1.1	3.3	0.0	22.9	14.2
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	14.5	7.4	22.3	0.0	173.0	122.7
LnGrp LOS	B	A	C		F	F
Approach Vol, veh/h		528	198	A	814	
Approach Delay, s/veh		12.6	22.3		152.1	
Approach LOS		B	C		F	
Timer - Assigned Phs	1	2		4		6
Phs Duration (G+Y+Rc), s	25.0	45.0		30.0		70.0
Change Period (Y+Rc), s	6.5	6.4		7.3		6.4
Max Green Setting (Gmax), s	18.5	38.6		22.7		38.6
Max Q Clear Time (g_c+I1), s	14.4	9.8		24.7		5.1
Green Ext Time (p_c), s	0.5	1.1		0.0		0.7

Intersection Summary

HCM 6th Ctrl Delay	87.6
HCM 6th LOS	F

Notes

Unsignalized Delay for [NWR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th Signalized Intersection Summary

1: SR 19 & CR 48

02/19/2019

						
Movement	SEL	SET	NWT	NWR	SWL	SWR
Lane Configurations						
Traffic Volume (veh/h)	335	124	172	479	413	295
Future Volume (veh/h)	335	124	172	479	413	295
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00			1.00	1.00	1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No	No		No	
Adj Sat Flow, veh/h/ln	1737	1811	1767	1811	1752	1589
Adj Flow Rate, veh/h	385	143	198	0	475	339
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	11	6	9	6	10	21
Cap, veh/h	540	880	382		629	508
Arrive On Green	0.20	0.49	0.22	0.00	0.38	0.38
Sat Flow, veh/h	1654	1811	1767	1535	1668	1346
Grp Volume(v), veh/h	385	143	198	0	475	339
Grp Sat Flow(s),veh/h/ln	1654	1811	1767	1535	1668	1346
Q Serve(g_s), s	17.0	4.4	9.9	0.0	24.8	21.0
Cycle Q Clear(g_c), s	17.0	4.4	9.9	0.0	24.8	21.0
Prop In Lane	1.00			1.00	1.00	1.00
Lane Grp Cap(c), veh/h	540	880	382		629	508
V/C Ratio(X)	0.71	0.16	0.52		0.76	0.67
Avail Cap(c_a), veh/h	540	880	382		629	508
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	0.00	1.00	1.00
Uniform Delay (d), s/veh	21.5	14.3	34.6	0.0	27.1	25.9
Incr Delay (d2), s/veh	7.8	0.4	5.0	0.0	8.2	6.8
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	7.2	1.8	4.7	0.0	10.6	7.2
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	29.3	14.7	39.6	0.0	35.3	32.8
LnGrp LOS	C	B	D		D	C
Approach Vol, veh/h		528	198	A	814	
Approach Delay, s/veh		25.3	39.6		34.3	
Approach LOS		C	D		C	
Timer - Assigned Phs	1	2		4		6
Phs Duration (G+Y+Rc), s	27.0	28.0		45.0		55.0
Change Period (Y+Rc), s	6.5	6.4		7.3		6.4
Max Green Setting (Gmax), s	20.5	21.6		37.7		48.6
Max Q Clear Time (g_c+I1), s	19.0	11.9		26.8		6.4
Green Ext Time (p_c), s	0.2	0.7		2.2		0.7
Intersection Summary						
HCM 6th Ctrl Delay			31.9			
HCM 6th LOS			C			

Notes

Unsignalized Delay for [NWR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th TWSC
2: SR 19 & W Central Ave/E Central Ave

02/19/2019

Intersection												
Int Delay, s/veh	14.9											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	74	9	60	11	9	8	32	522	19	22	448	37
Future Vol, veh/h	74	9	60	11	9	8	32	522	19	22	448	37
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	86	86	86	86	86	86	86	86	86	86	86	86
Heavy Vehicles, %	12	33	2	2	2	2	38	10	2	42	2	11
Mvmt Flow	86	10	70	13	10	9	37	607	22	26	521	43

Major/Minor	Minor2		Minor1		Major1			Major2				
Conflicting Flow All	1297	1298	543	1327	1308	618	564	0	0	629	0	0
Stage 1	595	595	-	692	692	-	-	-	-	-	-	-
Stage 2	702	703	-	635	616	-	-	-	-	-	-	-
Critical Hdwy	7.22	6.83	6.22	7.12	6.52	6.22	4.48	-	-	4.52	-	-
Critical Hdwy Stg 1	6.22	5.83	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.22	5.83	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.608	4.297	3.318	3.518	4.018	3.318	2.542	-	-	2.578	-	-
Pot Cap-1 Maneuver	132	140	540	132	159	489	851	-	-	787	-	-
Stage 1	474	446	-	434	445	-	-	-	-	-	-	-
Stage 2	413	397	-	467	482	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	112	124	540	98	141	489	851	-	-	787	-	-
Mov Cap-2 Maneuver	112	124	-	98	141	-	-	-	-	-	-	-
Stage 1	442	425	-	405	415	-	-	-	-	-	-	-
Stage 2	368	370	-	378	459	-	-	-	-	-	-	-

Approach	EB		WB		NB			SB				
HCM Control Delay, s	119.9		36.6		0.5			0.4				
HCM LOS	F		E									

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	851	-	-	169	146	787	-
HCM Lane V/C Ratio	0.044	-	-	0.984	0.223	0.033	-
HCM Control Delay (s)	9.4	0	-	119.9	36.6	9.7	0
HCM Lane LOS	A	A	-	F	E	A	A
HCM 95th %tile Q(veh)	0.1	-	-	7.7	0.8	0.1	-

HCM 6th TWSC
3: SR 19 & S Florida Ave

02/19/2019

Intersection												
Int Delay, s/veh	2.3											
Movement	NBL	NBT	NBR	SBL	SBT	SBR	NEL	NET	NER	SWL	SWT	SWR
Lane Configurations		↱	↱		↱		↱	↱	↱	↱	↱	
Traffic Vol, veh/h	36	3	21	7	4	23	21	559	14	9	514	2
Future Vol, veh/h	36	3	21	7	4	23	21	559	14	9	514	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	0	-	-	-	250	-	250	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	93	93	93	93	93	93	93	93	93	93	93	93
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	39	3	23	8	4	25	23	601	15	10	553	2

Major/Minor	Minor1		Minor2		Major1		Major2					
Conflicting Flow All	1236	1222	601	1242	1236	554	555	0	0	616	0	0
Stage 1	647	647	-	574	574	-	-	-	-	-	-	-
Stage 2	589	575	-	668	662	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	153	180	500	152	176	532	1015	-	-	964	-	-
Stage 1	460	467	-	504	503	-	-	-	-	-	-	-
Stage 2	494	503	-	448	459	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	140	174	500	140	170	532	1015	-	-	964	-	-
Mov Cap-2 Maneuver	140	174	-	140	170	-	-	-	-	-	-	-
Stage 1	449	456	-	492	498	-	-	-	-	-	-	-
Stage 2	462	498	-	415	448	-	-	-	-	-	-	-

Approach	NB		SB		NE		SW	
HCM Control Delay, s	30.8		19.1		0.3		0.2	
HCM LOS	D		C					

Minor Lane/Major Mvmt	NEL	NET	NER	NBLn1	NBLn2	SBLn1	SWL	SWT	SWR
Capacity (veh/h)	1015	-	-	142	500	291	964	-	-
HCM Lane V/C Ratio	0.022	-	-	0.295	0.045	0.126	0.01	-	-
HCM Control Delay (s)	8.6	-	-	40.6	12.5	19.1	8.8	-	-
HCM Lane LOS	A	-	-	E	B	C	A	-	-
HCM 95th %tile Q(veh)	0.1	-	-	1.2	0.1	0.4	0	-	-

HCM 6th TWSC
5: Orange Blossom Rd & SR 19

02/19/2019

Intersection

Int Delay, s/veh 3.8

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	47	55	21	663	611	21
Future Vol, veh/h	47	55	21	663	611	21
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	8	10	2
Mvmt Flow	55	65	25	780	719	25

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	1562	732	744
Stage 1	732	-	-
Stage 2	830	-	-
Critical Hdwy	6.42	6.22	4.12
Critical Hdwy Stg 1	5.42	-	-
Critical Hdwy Stg 2	5.42	-	-
Follow-up Hdwy	3.518	3.318	2.218
Pot Cap-1 Maneuver	123	421	864
Stage 1	476	-	-
Stage 2	428	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	117	421	864
Mov Cap-2 Maneuver	117	-	-
Stage 1	452	-	-
Stage 2	428	-	-

Approach	EB	NB	SB
HCM Control Delay, s	50.7	0.3	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	864	-	192	-	-
HCM Lane V/C Ratio	0.029	-	0.625	-	-
HCM Control Delay (s)	9.3	0	50.7	-	-
HCM Lane LOS	A	A	F	-	-
HCM 95th %tile Q(veh)	0.1	-	3.6	-	-

HCM 6th TWSC
5: Orange Blossom Rd & SR 19

02/19/2019

Intersection

Int Delay, s/veh 1.9

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	60	70	21	663	611	21
Future Vol, veh/h	60	70	21	663	611	21
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	145	400	-	-	350
Veh in Median Storage, #	1	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	8	10	2
Mvmt Flow	71	82	25	780	719	25

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	1549	719	744
Stage 1	719	-	-
Stage 2	830	-	-
Critical Hdwy	6.42	6.22	4.12
Critical Hdwy Stg 1	5.42	-	-
Critical Hdwy Stg 2	5.42	-	-
Follow-up Hdwy	3.518	3.318	2.218
Pot Cap-1 Maneuver	125	428	864
Stage 1	483	-	-
Stage 2	428	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	121	428	864
Mov Cap-2 Maneuver	259	-	-
Stage 1	469	-	-
Stage 2	428	-	-

Approach	EB	NB	SB
HCM Control Delay, s	19.4	0.3	0
HCM LOS	C		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	864	-	259	428	-	-
HCM Lane V/C Ratio	0.029	-	0.273	0.192	-	-
HCM Control Delay (s)	9.3	-	24	15.4	-	-
HCM Lane LOS	A	-	C	C	-	-
HCM 95th %tile Q(veh)	0.1	-	1.1	0.7	-	-

Intersection

Int Delay, s/veh 24.7

Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	111	105	553	106	143	640
Future Vol, veh/h	111	105	553	106	143	640
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	225	-	385	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	38	15	8	22	9	5
Mvmt Flow	114	108	570	109	147	660

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	1524	570	0
Stage 1	570	-	-
Stage 2	954	-	-
Critical Hdwy	6.78	6.35	-
Critical Hdwy Stg 1	5.78	-	-
Critical Hdwy Stg 2	5.78	-	-
Follow-up Hdwy	3.842	3.435	-
Pot Cap-1 Maneuver	~ 108	497	-
Stage 1	501	-	-
Stage 2	323	-	-
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	~ 80	497	-
Mov Cap-2 Maneuver	~ 80	-	-
Stage 1	501	-	-
Stage 2	238	-	-

Approach	WB	NB	SB
HCM Control Delay, s	183	0	1.8
HCM LOS	F		

Minor Lane/Major Mvmt	NBT	NBRWBLn1WBLn2	SBL	SBT
Capacity (veh/h)	-	- 80 497	881	-
HCM Lane V/C Ratio	-	- 1.43 0.218	0.167	-
HCM Control Delay (s)	-	- \$ 342.7	14.2	9.9
HCM Lane LOS	-	- F B	A	A
HCM 95th %tile Q(veh)	-	- 9	0.8	0.6

Notes

~: Volume exceeds capacity \$: Delay exceeds 300s +: Computation Not Defined *: All major volume in platoon

HCM 6th Signalized Intersection Summary

7: SR 19 Off Ramp/Turn Pike Off Ramp & US 27

02/19/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	271	968	36	52	1033	154	83	280	175	152	111	198
Future Volume (veh/h)	271	968	36	52	1033	154	83	280	175	152	111	198
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1796	1841	1648	1826	1841	1722	1870	1870	1870	1841	1870	1841
Adj Flow Rate, veh/h	291	1041	0	56	1111	0	89	301	0	163	119	0
Peak Hour Factor	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
Percent Heavy Veh, %	7	4	17	5	4	12	2	2	2	4	2	4
Cap, veh/h	271	1062		275	1062		106	271		386	715	
Arrive On Green	0.16	0.30	0.00	0.16	0.30	0.00	0.20	0.20	0.00	0.13	0.38	0.00
Sat Flow, veh/h	1711	3497	1397	1739	3497	1459	368	1330	1585	1753	1870	1560
Grp Volume(v), veh/h	291	1041	0	56	1111	0	390	0	0	163	119	0
Grp Sat Flow(s),veh/h/ln	1711	1749	1397	1739	1749	1459	1698	0	1585	1753	1870	1560
Q Serve(g_s), s	22.2	41.3	0.0	3.9	42.5	0.0	27.2	0.0	0.0	9.3	5.9	0.0
Cycle Q Clear(g_c), s	22.2	41.3	0.0	3.9	42.5	0.0	28.5	0.0	0.0	9.3	5.9	0.0
Prop In Lane	1.00		1.00	1.00		1.00	0.23		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	271	1062		275	1062		377	0		386	715	
V/C Ratio(X)	1.07	0.98		0.20	1.05		1.03	0.00		0.42	0.17	
Avail Cap(c_a), veh/h	271	1062		275	1062		377	0		386	715	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	58.9	48.3	0.0	51.3	48.7	0.0	56.9	0.0	0.0	32.6	28.5	0.0
Incr Delay (d2), s/veh	75.3	23.3	0.0	1.7	40.6	0.0	55.4	0.0	0.0	3.4	0.5	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	14.9	20.5	0.0	1.8	23.6	0.0	19.3	0.0	0.0	4.3	2.8	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	134.2	71.7	0.0	53.0	89.3	0.0	112.3	0.0	0.0	36.0	29.0	0.0
LnGrp LOS	F	E		D	F		F	A		D	C	
Approach Vol, veh/h		1332	A		1167	A		390	A		282	A
Approach Delay, s/veh		85.3			87.6			112.3			33.0	
Approach LOS		F			F			F			C	
Timer - Assigned Phs	1	2		4	5	6	7	8				
Phs Duration (G+Y+Rc), s	30.0	50.0		60.0	30.0	50.0	25.0	35.0				
Change Period (Y+Rc), s	* 7.8	7.5		6.5	7.9	7.5	6.5	6.5				
Max Green Setting (Gmax), s	* 22	42.5		28.5	22.1	42.5	18.5	28.5				
Max Q Clear Time (g_c+I1), s	24.2	44.5		7.9	5.9	43.3	11.3	30.5				
Green Ext Time (p_c), s	0.0	0.0		0.5	0.1	0.0	0.2	0.0				
Intersection Summary												
HCM 6th Ctrl Delay			84.8									
HCM 6th LOS			F									
Notes												
* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.												
Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.												

HCM 6th Signalized Intersection Summary

7: SR 19 Off Ramp/Turn Pike Off Ramp & US 27

02/19/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	271	968	36	52	1033	154	83	280	175	152	111	198
Future Volume (veh/h)	271	968	36	52	1033	154	83	280	175	152	111	198
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1796	1841	1648	1826	1841	1722	1870	1870	1870	1841	1870	1841
Adj Flow Rate, veh/h	291	1041	0	56	1111	0	89	301	0	163	119	0
Peak Hour Factor	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
Percent Heavy Veh, %	7	4	17	5	4	12	2	2	2	4	2	4
Cap, veh/h	296	1481		128	1137		121	329		279	648	
Arrive On Green	0.17	0.42	0.00	0.07	0.32	0.00	0.25	0.25	0.00	0.05	0.35	0.00
Sat Flow, veh/h	1711	3497	1397	1739	3497	1459	363	1337	1585	1753	1870	1560
Grp Volume(v), veh/h	291	1041	0	56	1111	0	390	0	0	163	119	0
Grp Sat Flow(s),veh/h/ln	1711	1749	1397	1739	1749	1459	1700	0	1585	1753	1870	1560
Q Serve(g_s), s	23.7	34.2	0.0	4.3	44.0	0.0	29.4	0.0	0.0	7.5	6.2	0.0
Cycle Q Clear(g_c), s	23.7	34.2	0.0	4.3	44.0	0.0	31.4	0.0	0.0	7.5	6.2	0.0
Prop In Lane	1.00		1.00	1.00		1.00	0.23		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	296	1481		128	1137		451	0		279	648	
V/C Ratio(X)	0.98	0.70		0.44	0.98		0.87	0.00		0.58	0.18	
Avail Cap(c_a), veh/h	296	1481		128	1137		451	0		279	648	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	57.7	33.1	0.0	62.1	46.7	0.0	51.5	0.0	0.0	37.1	31.9	0.0
Incr Delay (d2), s/veh	48.5	2.8	0.0	10.5	21.8	0.0	19.5	0.0	0.0	8.7	0.6	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	13.9	14.2	0.0	2.2	21.5	0.0	15.7	0.0	0.0	1.5	2.9	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	106.2	35.9	0.0	72.6	68.5	0.0	71.0	0.0	0.0	45.8	32.6	0.0
LnGrp LOS	F	D		E	E		E	A		D	C	
Approach Vol, veh/h	1332		A	1167		A	390		A	282		A
Approach Delay, s/veh	51.3			68.7			71.0			40.2		
Approach LOS	D			E			E			D		
Timer - Assigned Phs	1	2		4	5	6	7	8				
Phs Duration (G+Y+Rc), s	32.0	53.0		55.0	18.2	66.8	14.0	41.0				
Change Period (Y+Rc), s	* 7.8	7.5		6.5	7.9	7.5	6.5	6.5				
Max Green Setting (Gmax), s	* 24	45.5		48.5	10.3	59.3	7.5	34.5				
Max Q Clear Time (g_c+I1), s	25.7	46.0		8.2	6.3	36.2	9.5	33.4				
Green Ext Time (p_c), s	0.0	0.0		0.6	0.0	6.8	0.0	0.3				

Intersection Summary

HCM 6th Ctrl Delay 59.1

HCM 6th LOS E

Notes

* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th TWSC
8: US 27 & SR 19 Off Ramp

02/19/2019

Intersection						
Int Delay, s/veh	1.8					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	173	1145	1051	153	59	189
Future Vol, veh/h	173	1145	1051	153	59	189
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	Free	-	Free
Storage Length	320	-	-	480	0	0
Veh in Median Storage, #	-	0	0	-	2	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	3	3	4	5	2	6
Mvmt Flow	178	1180	1084	158	61	195
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	1084	0	-	0	2030	-
Stage 1	-	-	-	-	1084	-
Stage 2	-	-	-	-	946	-
Critical Hdwy	4.16	-	-	-	6.84	-
Critical Hdwy Stg 1	-	-	-	-	5.84	-
Critical Hdwy Stg 2	-	-	-	-	5.84	-
Follow-up Hdwy	2.23	-	-	-	3.52	-
Pot Cap-1 Maneuver	633	-	-	0	~ 50	0
Stage 1	-	-	-	0	286	0
Stage 2	-	-	-	0	338	0
Platoon blocked, %		-	-			
Mov Cap-1 Maneuver	633	-	-	-	~ 36	-
Mov Cap-2 Maneuver	-	-	-	-	168	-
Stage 1	-	-	-	-	206	-
Stage 2	-	-	-	-	338	-
Approach	EB	WB		SB		
HCM Control Delay, s	1.7	0		38.1		
HCM LOS	E					
Minor Lane/Major Mvmt	EBL	EBT	WBT	SBLn1	SBLn2	
Capacity (veh/h)	633	-	-	168	-	
HCM Lane V/C Ratio	0.282	-	-	0.362	-	
HCM Control Delay (s)	12.9	-	-	38.1	0	
HCM Lane LOS	B	-	-	E	A	
HCM 95th %tile Q(veh)	1.2	-	-	1.5	-	
Notes						
~: Volume exceeds capacity		\$: Delay exceeds 300s		+: Computation Not Defined		*: All major volume in platoon

Intersection

Int Delay, s/veh 5.2

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	48	6	32	46	17	96
Future Vol, veh/h	48	6	32	46	17	96
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	52	7	35	50	18	104

Major/Minor	Major1	Major2	Minor1
Conflicting Flow All	0	0	59
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	-	-	4.12
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	-	-	2.218
Pot Cap-1 Maneuver	-	-	1545
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	-	1545
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

Approach	EB	WB	NB
HCM Control Delay, s	0	3	9.2
HCM LOS			A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	971	-	-	1545	-
HCM Lane V/C Ratio	0.126	-	-	0.023	-
HCM Control Delay (s)	9.2	-	-	7.4	0
HCM Lane LOS	A	-	-	A	A
HCM 95th %tile Q(veh)	0.4	-	-	0.1	-

Intersection

Int Delay, s/veh 1.5

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	54	60	19	704	572	19
Future Vol, veh/h	54	60	19	704	572	19
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	400	-	-	350
Veh in Median Storage, #	1	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	59	65	21	765	622	21

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	1429	622	643
Stage 1	622	-	-
Stage 2	807	-	-
Critical Hdwy	6.42	6.22	4.12
Critical Hdwy Stg 1	5.42	-	-
Critical Hdwy Stg 2	5.42	-	-
Follow-up Hdwy	3.518	3.318	2.218
Pot Cap-1 Maneuver	149	487	942
Stage 1	535	-	-
Stage 2	439	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	146	487	942
Mov Cap-2 Maneuver	284	-	-
Stage 1	523	-	-
Stage 2	439	-	-

Approach	EB	NB	SB
HCM Control Delay, s	17	0.2	0
HCM LOS	C		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	942	-	284	487	-	-
HCM Lane V/C Ratio	0.022	-	0.207	0.134	-	-
HCM Control Delay (s)	8.9	-	20.9	13.5	-	-
HCM Lane LOS	A	-	C	B	-	-
HCM 95th %tile Q(veh)	0.1	-	0.8	0.5	-	-

Intersection

Int Delay, s/veh 6.1

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		↑	↑		↓	
Traffic Vol, veh/h	0	17	5	37	113	0
Future Vol, veh/h	0	17	5	37	113	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	18	5	40	123	0

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	-	0	43
Stage 1	-	-	25
Stage 2	-	-	18
Critical Hdwy	-	-	6.42
Critical Hdwy Stg 1	-	-	5.42
Critical Hdwy Stg 2	-	-	5.42
Follow-up Hdwy	-	-	3.518
Pot Cap-1 Maneuver	0	-	968
Stage 1	0	-	998
Stage 2	0	-	1005
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	-	968
Mov Cap-2 Maneuver	-	-	968
Stage 1	-	-	998
Stage 2	-	-	1005

Approach	EB	WB	SB
HCM Control Delay, s	0	0	9.3
HCM LOS			A

Minor Lane/Major Mvmt	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	-	-	-	968
HCM Lane V/C Ratio	-	-	-	0.127
HCM Control Delay (s)	-	-	-	9.3
HCM Lane LOS	-	-	-	A
HCM 95th %tile Q(veh)	-	-	-	0.4

HCM 6th Signalized Intersection Summary

1: SR 19 & CR 48

02/19/2019



Movement	SEL	SET	NWT	NWR	SWL	SWR
Lane Configurations						
Traffic Volume (veh/h)	347	152	147	449	577	490
Future Volume (veh/h)	347	152	147	449	577	490
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00			1.00	1.00	1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No	No		No	
Adj Sat Flow, veh/h/ln	1737	1811	1767	1811	1752	1589
Adj Flow Rate, veh/h	399	175	169	0	663	563
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	11	6	9	6	10	21
Cap, veh/h	741	1152	682		379	306
Arrive On Green	0.19	0.64	0.39	0.00	0.23	0.23
Sat Flow, veh/h	1654	1811	1767	1535	1668	1346
Grp Volume(v), veh/h	399	175	169	0	663	563
Grp Sat Flow(s),veh/h/ln	1654	1811	1767	1535	1668	1346
Q Serve(g_s), s	13.0	3.9	6.5	0.0	22.7	22.7
Cycle Q Clear(g_c), s	13.0	3.9	6.5	0.0	22.7	22.7
Prop In Lane	1.00			1.00	1.00	1.00
Lane Grp Cap(c), veh/h	741	1152	682		379	306
V/C Ratio(X)	0.54	0.15	0.25		1.75	1.84
Avail Cap(c_a), veh/h	741	1152	682		379	306
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	0.00	1.00	1.00
Uniform Delay (d), s/veh	11.6	7.3	20.8	0.0	38.7	38.7
Incr Delay (d2), s/veh	2.8	0.3	0.9	0.0	348.5	391.4
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	4.7	1.4	2.8	0.0	45.4	40.3
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	14.4	7.6	21.7	0.0	387.2	430.0
LnGrp LOS	B	A	C		F	F
Approach Vol, veh/h		574	169	A	1226	
Approach Delay, s/veh		12.3	21.7		406.9	
Approach LOS		B	C		F	
Timer - Assigned Phs	1	2		4		6
Phs Duration (G+Y+Rc), s	25.0	45.0		30.0		70.0
Change Period (Y+Rc), s	6.5	6.4		7.3		6.4
Max Green Setting (Gmax), s	18.5	38.6		22.7		38.6
Max Q Clear Time (g_c+I1), s	15.0	8.5		24.7		5.9
Green Ext Time (p_c), s	0.5	0.9		0.0		0.9

Intersection Summary

HCM 6th Ctrl Delay 258.8

HCM 6th LOS F

Notes

Unsignalized Delay for [NWR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th Signalized Intersection Summary

1: SR 19 & CR 48

02/19/2019

						
Movement	SEL	SET	NWT	NWR	SWL	SWR
Lane Configurations						
Traffic Volume (veh/h)	347	152	147	449	577	490
Future Volume (veh/h)	347	152	147	449	577	490
Initial Q (Qb), veh	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00			1.00	1.00	1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No	No		No	
Adj Sat Flow, veh/h/ln	1737	1811	1767	1811	1752	1589
Adj Flow Rate, veh/h	399	175	169	0	663	563
Peak Hour Factor	0.87	0.87	0.87	0.87	0.87	0.87
Percent Heavy Veh, %	11	6	9	6	10	21
Cap, veh/h	454	753	346		746	602
Arrive On Green	0.16	0.42	0.20	0.00	0.45	0.45
Sat Flow, veh/h	1654	1811	1767	1535	1668	1346
Grp Volume(v), veh/h	399	175	169	0	663	563
Grp Sat Flow(s),veh/h/ln	1654	1811	1767	1535	1668	1346
Q Serve(g_s), s	15.5	6.2	8.5	0.0	36.5	39.7
Cycle Q Clear(g_c), s	15.5	6.2	8.5	0.0	36.5	39.7
Prop In Lane	1.00			1.00	1.00	1.00
Lane Grp Cap(c), veh/h	454	753	346		746	602
V/C Ratio(X)	0.88	0.23	0.49		0.89	0.94
Avail Cap(c_a), veh/h	454	753	346		746	602
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	1.00	0.00	1.00	1.00
Uniform Delay (d), s/veh	29.4	18.9	35.7	0.0	25.4	26.3
Incr Delay (d2), s/veh	20.9	0.7	4.9	0.0	14.9	23.8
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	4.7	2.6	4.1	0.0	16.1	15.4
Unsig. Movement Delay, s/veh						
LnGrp Delay(d),s/veh	50.3	19.6	40.6	0.0	40.3	50.1
LnGrp LOS	D	B	D		D	D
Approach Vol, veh/h		574	169	A	1226	
Approach Delay, s/veh		40.9	40.6		44.8	
Approach LOS		D	D		D	
Timer - Assigned Phs	1	2		4		6
Phs Duration (G+Y+Rc), s	22.0	26.0		52.0		48.0
Change Period (Y+Rc), s	6.5	6.4		7.3		6.4
Max Green Setting (Gmax), s	15.5	19.6		44.7		41.6
Max Q Clear Time (g_c+I1), s	17.5	10.5		41.7		8.2
Green Ext Time (p_c), s	0.0	0.5		1.5		0.9
Intersection Summary						
HCM 6th Ctrl Delay			43.3			
HCM 6th LOS			D			

Notes

Unsignalized Delay for [NWR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th TWSC
2: SR 19 & W Central Ave/E Central Ave

02/19/2019

Intersection												
Int Delay, s/veh	34.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	70	11	46	13	11	10	66	517	12	15	594	85
Future Vol, veh/h	70	11	46	13	11	10	66	517	12	15	594	85
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	86	86	86	86	86	86	86	86	86	86	86	86
Heavy Vehicles, %	12	33	2	2	2	2	38	10	2	42	2	11
Mvmt Flow	81	13	53	15	13	12	77	601	14	17	691	99

Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	1550	1544	741	1570	1586	608	790	0	0	615	0	0
Stage 1	775	775	-	762	762	-	-	-	-	-	-	-
Stage 2	775	769	-	808	824	-	-	-	-	-	-	-
Critical Hdwy	7.22	6.83	6.22	7.12	6.52	6.22	4.48	-	-	4.52	-	-
Critical Hdwy Stg 1	6.22	5.83	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.22	5.83	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.608	4.297	3.318	3.518	4.018	3.318	2.542	-	-	2.578	-	-
Pot Cap-1 Maneuver	88	98	416	90	108	496	691	-	-	798	-	-
Stage 1	376	366	-	397	414	-	-	-	-	-	-	-
Stage 2	376	369	-	375	387	-	-	-	-	-	-	-
Platoon blocked, %								-	-	-	-	-
Mov Cap-1 Maneuver	~ 65	78	416	58	86	496	691	-	-	798	-	-
Mov Cap-2 Maneuver	~ 65	78	-	58	86	-	-	-	-	-	-	-
Stage 1	312	352	-	330	344	-	-	-	-	-	-	-
Stage 2	293	306	-	303	372	-	-	-	-	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s\$	365.2	72	1.2	0.2
HCM LOS	F	F		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	691	-	-	96	91	798	-
HCM Lane V/C Ratio	0.111	-	-	1.538	0.434	0.022	-
HCM Control Delay (s)	10.9	0	-	\$ 365.2	72	9.6	0
HCM Lane LOS	B	A	-	F	F	A	A
HCM 95th %tile Q(veh)	0.4	-	-	11.3	1.8	0.1	-

Notes			
-: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

HCM 6th TWSC
3: SR 19 & S Florida Ave

02/19/2019

Intersection												
Int Delay, s/veh	1.2											
Movement	NBL	NBT	NBR	SBL	SBT	SBR	NEL	NET	NER	SWL	SWT	SWR
Lane Configurations		↰	↱		↰		↰	↱	↱	↰	↱	
Traffic Vol, veh/h	14	2	14	3	4	12	12	577	16	20	634	2
Future Vol, veh/h	14	2	14	3	4	12	12	577	16	20	634	2
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	0	-	-	-	250	-	250	250	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	93	93	93	93	93	93	93	93	93	93	93	93
Heavy Vehicles, %	2	2	2	2	2	2	2	2	2	2	2	2
Mvmt Flow	15	2	15	3	4	13	13	620	17	22	682	2

Major/Minor	Minor1		Minor2		Major1		Major2					
Conflicting Flow All	1382	1374	620	1390	1390	683	684	0	0	637	0	0
Stage 1	646	646	-	727	727	-	-	-	-	-	-	-
Stage 2	736	728	-	663	663	-	-	-	-	-	-	-
Critical Hdwy	7.12	6.52	6.22	7.12	6.52	6.22	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.12	5.52	-	6.12	5.52	-	-	-	-	-	-	-
Follow-up Hdwy	3.518	4.018	3.318	3.518	4.018	3.318	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	121	145	488	120	142	449	909	-	-	947	-	-
Stage 1	460	467	-	415	429	-	-	-	-	-	-	-
Stage 2	411	429	-	450	459	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	111	140	488	112	137	449	909	-	-	947	-	-
Mov Cap-2 Maneuver	111	140	-	112	137	-	-	-	-	-	-	-
Stage 1	454	460	-	409	419	-	-	-	-	-	-	-
Stage 2	386	419	-	428	453	-	-	-	-	-	-	-

Approach	NB		SB		NE		SW	
HCM Control Delay, s	28.3		22.2		0.2		0.3	
HCM LOS	D		C					

Minor Lane/Major Mvmt	NEL	NET	NER	NBLn1	NBLn2	SBLn1	SWL	SWT	SWR
Capacity (veh/h)	909	-	-	114	488	230	947	-	-
HCM Lane V/C Ratio	0.014	-	-	0.151	0.031	0.089	0.023	-	-
HCM Control Delay (s)	9	-	-	42.1	12.6	22.2	8.9	-	-
HCM Lane LOS	A	-	-	E	B	C	A	-	-
HCM 95th %tile Q(veh)	0	-	-	0.5	0.1	0.3	0.1	-	-

HCM 6th TWSC
5: Orange Blossom Rd & SR 19

02/19/2019

Intersection

Int Delay, s/veh 6

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	41	41	71	673	676	68
Future Vol, veh/h	41	41	71	673	676	68
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	8	10	2
Mvmt Flow	48	48	84	792	795	80

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	1795	835	875
Stage 1	835	-	-
Stage 2	960	-	-
Critical Hdwy	6.42	6.22	4.12
Critical Hdwy Stg 1	5.42	-	-
Critical Hdwy Stg 2	5.42	-	-
Follow-up Hdwy	3.518	3.318	2.218
Pot Cap-1 Maneuver	88	368	771
Stage 1	426	-	-
Stage 2	372	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	71	368	771
Mov Cap-2 Maneuver	71	-	-
Stage 1	343	-	-
Stage 2	372	-	-

Approach	EB	NB	SB
HCM Control Delay, s	106	1	0
HCM LOS	F		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	SBT	SBR
Capacity (veh/h)	771	-	119	-	-
HCM Lane V/C Ratio	0.108	-	0.811	-	-
HCM Control Delay (s)	10.2	0	106	-	-
HCM Lane LOS	B	A	F	-	-
HCM 95th %tile Q(veh)	0.4	-	4.8	-	-

HCM 6th TWSC
5: Orange Blossom Rd & SR 19

02/19/2019

Intersection

Int Delay, s/veh 1.6

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	41	41	71	673	676	68
Future Vol, veh/h	41	41	71	673	676	68
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	145	400	-	-	350
Veh in Median Storage, #	1	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	85	85	85	85	85	85
Heavy Vehicles, %	2	2	2	8	10	2
Mvmt Flow	48	48	84	792	795	80

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	1755	795	875
Stage 1	795	-	-
Stage 2	960	-	-
Critical Hdwy	6.42	6.22	4.12
Critical Hdwy Stg 1	5.42	-	-
Critical Hdwy Stg 2	5.42	-	-
Follow-up Hdwy	3.518	3.318	2.218
Pot Cap-1 Maneuver	94	388	771
Stage 1	445	-	-
Stage 2	372	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	84	388	771
Mov Cap-2 Maneuver	213	-	-
Stage 1	396	-	-
Stage 2	372	-	-

Approach	EB	NB	SB
HCM Control Delay, s	21.2	1	0
HCM LOS	C		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	771	-	213	388	-	-
HCM Lane V/C Ratio	0.108	-	0.226	0.124	-	-
HCM Control Delay (s)	10.2	-	26.8	15.6	-	-
HCM Lane LOS	B	-	D	C	-	-
HCM 95th %tile Q(veh)	0.4	-	0.8	0.4	-	-

Intersection						
Int Delay, s/veh	52.1					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	116	137	768	114	125	733
Future Vol, veh/h	116	137	768	114	125	733
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	225	-	385	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	38	15	8	22	9	5
Mvmt Flow	120	141	792	118	129	756
Major/Minor	Minor1	Major1		Major2		
Conflicting Flow All	1806	792	0	0	910	0
Stage 1	792	-	-	-	-	-
Stage 2	1014	-	-	-	-	-
Critical Hdwy	6.78	6.35	-	-	4.19	-
Critical Hdwy Stg 1	5.78	-	-	-	-	-
Critical Hdwy Stg 2	5.78	-	-	-	-	-
Follow-up Hdwy	3.842	3.435	-	-	2.281	-
Pot Cap-1 Maneuver	~ 70	369	-	-	720	-
Stage 1	389	-	-	-	-	-
Stage 2	301	-	-	-	-	-
Platoon blocked, %			-	-		-
Mov Cap-1 Maneuver	~ 48	369	-	-	720	-
Mov Cap-2 Maneuver	~ 48	-	-	-	-	-
Stage 1	389	-	-	-	-	-
Stage 2	208	-	-	-	-	-
Approach	WB	NB		SB		
HCM Control Delay, s\$	405.1	0		1.6		
HCM LOS	F					
Minor Lane/Major Mvmt	NBT	NBR	WBLn1	WBLn2	SBL	SBT
Capacity (veh/h)	-	-	48	369	720	-
HCM Lane V/C Ratio	-	-	2.491	0.383	0.179	-
HCM Control Delay (s)	-	-	\$ 859.1	20.7	11.1	0
HCM Lane LOS	-	-	F	C	B	A
HCM 95th %tile Q(veh)	-	-	12.5	1.8	0.6	-
Notes						
~: Volume exceeds capacity		\$: Delay exceeds 300s		+: Computation Not Defined		*: All major volume in platoon

HCM 6th Signalized Intersection Summary

7: SR 19 Off Ramp/Turn Pike Off Ramp & US 27

02/19/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	370	974	64	154	938	110	112	114	185	380	277	228
Future Volume (veh/h)	370	974	64	154	938	110	112	114	185	380	277	228
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach		No			No			No			No	
Adj Sat Flow, veh/h/ln	1796	1841	1648	1826	1841	1722	1870	1870	1870	1841	1870	1841
Adj Flow Rate, veh/h	398	1047	0	166	1009	0	120	123	0	409	298	0
Peak Hour Factor	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
Percent Heavy Veh, %	7	4	17	5	4	12	2	2	2	4	2	4
Cap, veh/h	271	1062		275	1062		177	142		493	715	
Arrive On Green	0.16	0.30	0.00	0.16	0.30	0.00	0.20	0.20	0.00	0.13	0.38	0.00
Sat Flow, veh/h	1711	3497	1397	1739	3497	1459	679	696	1585	1753	1870	1560
Grp Volume(v), veh/h	398	1047	0	166	1009	0	243	0	0	409	298	0
Grp Sat Flow(s),veh/h/ln	1711	1749	1397	1739	1749	1459	1375	0	1585	1753	1870	1560
Q Serve(g_s), s	22.2	41.7	0.0	12.4	39.5	0.0	23.9	0.0	0.0	18.5	16.4	0.0
Cycle Q Clear(g_c), s	22.2	41.7	0.0	12.4	39.5	0.0	23.9	0.0	0.0	18.5	16.4	0.0
Prop In Lane	1.00		1.00	1.00		1.00	0.49		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	271	1062		275	1062		318	0		493	715	
V/C Ratio(X)	1.47	0.99		0.60	0.95		0.76	0.00		0.83	0.42	
Avail Cap(c_a), veh/h	271	1062		275	1062		318	0		493	715	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	58.9	48.5	0.0	54.9	47.7	0.0	53.9	0.0	0.0	40.2	31.8	0.0
Incr Delay (d2), s/veh	229.3	24.5	0.0	9.5	18.0	0.0	15.9	0.0	0.0	14.8	1.8	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	26.5	20.8	0.0	6.0	19.0	0.0	9.6	0.0	0.0	5.9	7.8	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	288.2	72.9	0.0	64.4	65.7	0.0	69.8	0.0	0.0	55.0	33.6	0.0
LnGrp LOS	F	E		E	E		E	A		E	C	
Approach Vol, veh/h		1445	A		1175	A		243	A		707	A
Approach Delay, s/veh		132.2			65.5			69.8			46.0	
Approach LOS		F			E			E			D	
Timer - Assigned Phs	1	2		4	5	6	7	8				
Phs Duration (G+Y+Rc), s	30.0	50.0		60.0	30.0	50.0	25.0	35.0				
Change Period (Y+Rc), s	* 7.8	7.5		6.5	7.9	7.5	6.5	6.5				
Max Green Setting (Gmax), s	* 22	42.5		28.5	22.1	42.5	18.5	28.5				
Max Q Clear Time (g_c+I1), s	24.2	41.5		18.4	14.4	43.7	20.5	25.9				
Green Ext Time (p_c), s	0.0	0.6		1.1	0.2	0.0	0.0	0.3				
Intersection Summary												
HCM 6th Ctrl Delay			89.0									
HCM 6th LOS			F									
Notes												
* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.												
Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.												

HCM 6th Signalized Intersection Summary

7: SR 19 Off Ramp/Turn Pike Off Ramp & US 27

02/19/2019

												
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Volume (veh/h)	370	974	64	154	938	110	112	114	185	380	277	228
Future Volume (veh/h)	370	974	64	154	938	110	112	114	185	380	277	228
Initial Q (Qb), veh	0	0	0	0	0	0	0	0	0	0	0	0
Ped-Bike Adj(A_pbT)	1.00		1.00	1.00		1.00	1.00		1.00	1.00		1.00
Parking Bus, Adj	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Work Zone On Approach	No			No			No			No		
Adj Sat Flow, veh/h/ln	1796	1841	1648	1826	1841	1722	1870	1870	1870	1841	1870	1841
Adj Flow Rate, veh/h	398	1047	0	166	1009	0	120	123	0	409	298	0
Peak Hour Factor	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93	0.93
Percent Heavy Veh, %	7	4	17	5	4	12	2	2	2	4	2	4
Cap, veh/h	345	1289		199	987		162	127		465	675	
Arrive On Green	0.20	0.37	0.00	0.11	0.28	0.00	0.18	0.18	0.00	0.13	0.36	0.00
Sat Flow, veh/h	1711	3497	1397	1739	3497	1459	679	696	1585	1753	1870	1560
Grp Volume(v), veh/h	398	1047	0	166	1009	0	243	0	0	409	298	0
Grp Sat Flow(s),veh/h/ln	1711	1749	1397	1739	1749	1459	1375	0	1585	1753	1870	1560
Q Serve(g_s), s	28.2	37.8	0.0	13.1	39.5	0.0	24.6	0.0	0.0	18.5	17.0	0.0
Cycle Q Clear(g_c), s	28.2	37.8	0.0	13.1	39.5	0.0	24.6	0.0	0.0	18.5	17.0	0.0
Prop In Lane	1.00		1.00	1.00		1.00	0.49		1.00	1.00		1.00
Lane Grp Cap(c), veh/h	345	1289		199	987		289	0		465	675	
V/C Ratio(X)	1.15	0.81		0.84	1.02		0.84	0.00		0.88	0.44	
Avail Cap(c_a), veh/h	345	1289		199	987		289	0		465	675	
HCM Platoon Ratio	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Upstream Filter(I)	1.00	1.00	0.00	1.00	1.00	0.00	1.00	0.00	0.00	1.00	1.00	0.00
Uniform Delay (d), s/veh	55.9	39.8	0.0	60.7	50.3	0.0	56.9	0.0	0.0	43.1	34.0	0.0
Incr Delay (d2), s/veh	97.6	5.7	0.0	32.1	34.5	0.0	24.6	0.0	0.0	20.5	2.1	0.0
Initial Q Delay(d3),s/veh	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
%ile BackOfQ(50%),veh/ln	21.0	16.4	0.0	7.3	21.1	0.0	10.4	0.0	0.0	7.2	8.1	0.0
Unsig. Movement Delay, s/veh												
LnGrp Delay(d),s/veh	153.5	45.5	0.0	92.8	84.7	0.0	81.5	0.0	0.0	63.7	36.1	0.0
LnGrp LOS	F	D		F	F		F	A		E	D	
Approach Vol, veh/h	1445		A	1175		A	243		A	707		A
Approach Delay, s/veh	75.2			85.9			81.5			52.1		
Approach LOS	E			F			F			D		
Timer - Assigned Phs	1	2		4	5	6	7	8				
Phs Duration (G+Y+Rc), s	36.0	47.0		57.0	23.9	59.1	25.0	32.0				
Change Period (Y+Rc), s	* 7.8	7.5		6.5	7.9	7.5	6.5	6.5				
Max Green Setting (Gmax), s	* 28	39.5		50.5	16.0	51.6	18.5	25.5				
Max Q Clear Time (g_c+I1), s	30.2	41.5		19.0	15.1	39.8	20.5	26.6				
Green Ext Time (p_c), s	0.0	0.0		1.8	0.0	5.0	0.0	0.0				

Intersection Summary

HCM 6th Ctrl Delay 74.6

HCM 6th LOS E

Notes

* HCM 6th computational engine requires equal clearance times for the phases crossing the barrier.

Unsignalized Delay for [NBR, EBR, WBR, SBR] is excluded from calculations of the approach delay and intersection delay.

HCM 6th TWSC
8: US 27 & SR 19 Off Ramp

02/19/2019

Intersection						
Int Delay, s/veh	2.5					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	226	1165	1048	238	62	111
Future Vol, veh/h	226	1165	1048	238	62	111
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	Free	-	Free
Storage Length	320	-	-	480	0	0
Veh in Median Storage, #	-	0	0	-	2	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	97	97	97	97	97	97
Heavy Vehicles, %	3	3	4	5	2	6
Mvmt Flow	233	1201	1080	245	64	114

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	1080	0	0 2147
Stage 1	-	-	- 1080
Stage 2	-	-	- 1067
Critical Hdwy	4.16	-	- 6.84
Critical Hdwy Stg 1	-	-	- 5.84
Critical Hdwy Stg 2	-	-	- 5.84
Follow-up Hdwy	2.23	-	- 3.52
Pot Cap-1 Maneuver	636	-	0 ~ 41
Stage 1	-	-	0 287
Stage 2	-	-	0 292
Platoon blocked, %	-	-	
Mov Cap-1 Maneuver	636	-	- ~ 26
Mov Cap-2 Maneuver	-	-	- 146
Stage 1	-	-	- 182
Stage 2	-	-	- 292

Approach	EB	WB	SB
HCM Control Delay, s	2.3	0	47.6
HCM LOS			E

Minor Lane/Major Mvmt	EBL	EBT	WBT	SBLn1	SBLn2
Capacity (veh/h)	636	-	-	146	-
HCM Lane V/C Ratio	0.366	-	-	0.438	-
HCM Control Delay (s)	13.9	-	-	47.6	0
HCM Lane LOS	B	-	-	E	A
HCM 95th %tile Q(veh)	1.7	-	-	2	-

Notes			
-: Volume exceeds capacity	\$: Delay exceeds 300s	+: Computation Not Defined	*: All major volume in platoon

Intersection

Int Delay, s/veh 4.8

Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations						
Traffic Vol, veh/h	54	19	105	57	11	62
Future Vol, veh/h	54	19	105	57	11	62
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	0	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	59	21	114	62	12	67

Major/Minor	Major1	Major2	Minor1
Conflicting Flow All	0	0	80
Stage 1	-	-	-
Stage 2	-	-	-
Critical Hdwy	-	-	4.12
Critical Hdwy Stg 1	-	-	-
Critical Hdwy Stg 2	-	-	-
Follow-up Hdwy	-	-	2.218
Pot Cap-1 Maneuver	-	-	1518
Stage 1	-	-	-
Stage 2	-	-	-
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	-	1518
Mov Cap-2 Maneuver	-	-	-
Stage 1	-	-	-
Stage 2	-	-	-

Approach	EB	WB	NB
HCM Control Delay, s	0	4.9	9.4
HCM LOS			A

Minor Lane/Major Mvmt	NBLn1	EBT	EBR	WBL	WBT
Capacity (veh/h)	900	-	-	1518	-
HCM Lane V/C Ratio	0.088	-	-	0.075	-
HCM Control Delay (s)	9.4	-	-	7.6	0
HCM Lane LOS	A	-	-	A	A
HCM 95th %tile Q(veh)	0.3	-	-	0.2	-

Intersection

Int Delay, s/veh 1.3

Movement	EBL	EBR	NBL	NBT	SBT	SBR
Lane Configurations						
Traffic Vol, veh/h	34	39	67	640	705	60
Future Vol, veh/h	34	39	67	640	705	60
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	0	400	-	-	350
Veh in Median Storage, #	1	-	-	0	0	-
Grade, %	0	-	-	0	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	37	42	73	696	766	65

Major/Minor	Minor2	Major1	Major2
Conflicting Flow All	1608	766	831
Stage 1	766	-	-
Stage 2	842	-	-
Critical Hdwy	6.42	6.22	4.12
Critical Hdwy Stg 1	5.42	-	-
Critical Hdwy Stg 2	5.42	-	-
Follow-up Hdwy	3.518	3.318	2.218
Pot Cap-1 Maneuver	115	403	801
Stage 1	459	-	-
Stage 2	423	-	-
Platoon blocked, %			
Mov Cap-1 Maneuver	105	403	801
Mov Cap-2 Maneuver	240	-	-
Stage 1	417	-	-
Stage 2	423	-	-

Approach	EB	NB	SB
HCM Control Delay, s	18.6	0.9	0
HCM LOS	C		

Minor Lane/Major Mvmt	NBL	NBT	EBLn1	EBLn2	SBT	SBR
Capacity (veh/h)	801	-	240	403	-	-
HCM Lane V/C Ratio	0.091	-	0.154	0.105	-	-
HCM Control Delay (s)	9.9	-	22.7	15	-	-
HCM Lane LOS	A	-	C	C	-	-
HCM 95th %tile Q(veh)	0.3	-	0.5	0.3	-	-

Intersection

Int Delay, s/veh 3.1

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	0	9	18	121	73	0
Future Vol, veh/h	0	9	18	121	73	0
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	92	92	92	92	92	92
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	10	20	132	79	0


Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	-	0	0 96 86
Stage 1	-	-	- 86 -
Stage 2	-	-	- 10 -
Critical Hdwy	-	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	-	-	- 3.518 3.318
Pot Cap-1 Maneuver	0	-	- 903 973
Stage 1	0	-	- 937 -
Stage 2	0	-	- 1013 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	-	-	- 903 973
Mov Cap-2 Maneuver	-	-	- 903 -
Stage 1	-	-	- 937 -
Stage 2	-	-	- 1013 -

Approach	EB	WB	SB
HCM Control Delay, s	0	0	9.4
HCM LOS			A

Minor Lane/Major Mvmt	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	-	-	-	903
HCM Lane V/C Ratio	-	-	-	0.088
HCM Control Delay (s)	-	-	-	9.4
HCM Lane LOS	-	-	-	A
HCM 95th %tile Q(veh)	-	-	-	0.3


Appendix J
FDOT Design Manual Exhibit FDM 212.1

MEDIAN TURN LANES
MINIMUM DECELERATION LENGTHS



DOUBLE LEFT TURN

Brakes Applied After Turning
Vehicle Clears Through Lane;
Entry Speed:
10 mph Below Design Speed
For Urban Condition
Average Running Speed For
Rural Condition



SINGLE LEFT TURN

Brakes Applied After Turning
Vehicle Clears Through Lane;
Entry Speed:
10 mph Below Design Speed
For Urban Condition
Average Running Speed For
Rural Condition

MEDIAN TURN LANES									
URBAN CONDITIONS					RURAL CONDITIONS				
Design Speed (mph)	Entry Speed (mph)	Clearance Distance L_1 (ft.)	Brake To Stop Distance L_2 (ft.)	Total Decel. Distance L (ft.)	Clearance Distance L_3 (ft.)	Brake To Stop Distance L_2 (ft.)	Total Decel. Distance L (ft.)	Clearance Distance L_3 (ft.)	
35	25	70	75	145	110	—	—	—	
40	30	80	75	155	120	—	—	—	
45	35	85	100	185	135	—	—	—	
50	40/44	105	135	240	160	185	290	160	
55	48	125	—	—	—	225	350	195	
60	52	145	—	—	—	260	405	230	
65	55	170	—	—	—	290	460	270	

NOT TO SCALE

Appendix K
NCHRP Report 457

Figure 2 - 6. Guideline for determining the need for a major-road right-turn bay at a two-way stop-controlled intersection.




Figure 2 - 6. Guideline for determining the need for a major-road right-turn bay at a two-way stop-controlled intersection.




Figure 2 - 6. Guideline for determining the need for a major-road right-turn bay at a two-way stop-controlled intersection.





Figure 2 - 5. Guideline for determining the need for a major-road left-turn bay at a two-way stop-controlled intersection.

2-lane roadway (English)




CALIBRATION CONSTANTS

Variable	Value
Average time for making left-turn, s:	3.0
Critical headway, s:	5.0
Average time for left-turn vehicle to clear the advancing lane, s:	1.9

Figure 2 - 5. Guideline for determining the need for a major-road left-turn bay at a two-way stop-controlled intersection.

2-lane roadway (English)



CALIBRATION CONSTANTS

Variable	Value
Average time for making left-turn, s:	3.0
Critical headway, s:	5.0
Average time for left-turn vehicle to clear the advancing lane, s:	1.9